

Rotating nozzles

R+M 150



1/4" F. Spray angle 17°. 50 - 150 bar. Max. 60 °C

R+M Nr.	D	C
653 325	025	green
653 330	03	yellow
653 335	035	black
653 340	04	blue
653 345	045	dark green

IP ROTOMAX



1/4" F. Housing black. Nozzle and seal kit ceramic. Adjustable spray angle. 100 - 250 bar. Max. 80 °C

R+M Nr.	DN	↔	C
996 050 01	1.4 mm	10 - 16 l/min	red
996 050 02	1.6 mm	12 - 18 l/min	blue
996 050 03	2.0 mm	14 - 21 l/min	black

Vario nozzles and triple nozzles

Vario nozzles



M22 M. Lance with vario nozzle. Zinc-plated steel. Max. 200 bar / 150 °C

R+M Nr.	D	C	↔	M*
658 103 03	03	yellow	430 mm	zinc-plated steel
658 103 53	035	white	430 mm	zinc-plated steel
658 104 03	04	blue	430 mm	zinc-plated steel
658 104 53	045	orange	430 mm	zinc-plated steel
658 105 03	05	green	430 mm	zinc-plated steel
658 105 53	055	black	430 mm	zinc-plated steel
658 106 03	06	grey	430 mm	zinc-plated steel

M22 M. Lance with vario nozzle. Stainless steel Max. 200 bar / 150 °C

R+M Nr.	D	C	↔	M*
658 103 039	03	yellow	430 mm	stainless steel
658 103 539	035	white	430 mm	stainless steel
658 104 039	04	blue	430 mm	stainless steel
658 104 539	045	orange	430 mm	stainless steel
658 105 039	05	green	430 mm	stainless steel
658 105 539	055	black	430 mm	stainless steel
658 106 039	06	grey	430 mm	stainless steel



1/4" F. Housing black. Max. 200 bar / 150 °C

R+M Nr.	D	C
658 103 0	03	yellow
658 103 5	035	white
658 104 0	04	blue
658 104 5	045	orange
658 105	05	green
658 105 5	055	black
658 106	06	grey



M18 F. Housing black. Max. 200 bar / 150 °C

R+M Nr.	D	C
658 103 04	03	yellow
658 103 54	035	white
658 104 04	04	blue
658 104 54	045	orange
658 105 04	05	green
658 105 54	055	black
658 106 04	06	grey

* lance

Functional principle vario nozzles

