

Suttner Rotordüsen mit Keramikeinsatz

ST-456



1/4" IG. Spritzwinkel 20°.
200 - 350 bar. Max. 100 °C

R+M Nr.	D	C
200 456 530	03	gelb
200 456 535	035	lila
200 456 540	04	braun
200 456 545	045	hellgrün
200 456 550	05	schwarz
200 456 555	055	hellblau
200 456 560	06	rot
200 456 565	065	natur
200 456 570	07	rosa
200 456 580	08	orange
200 456 590	09	grün



Kit ST-456

R+M Nr.
200 456 130
200 456 135
200 456 140
200 456 145
200 456 150
200 456 155
200 456 160
200 456 165
200 456 170
200 456 180
200 456 190



M18 IG. Spritzwinkel 20°.
200 - 350 bar. Max. 100 °C

R+M Nr.	D	C
200 456 630	03	gelb
200 456 635	035	lila
200 456 640	04	braun
200 456 645	045	hellgrün
200 456 650	05	schwarz
200 456 655	055	hellblau
200 456 660	06	rot
200 456 665	065	natur
200 456 670	07	rosa
200 456 680	08	orange
200 456 690	09	grün



Kit ST-456


R+M Nr.
200 456 130
200 456 135
200 456 140
200 456 145
200 456 150
200 456 155
200 456 160
200 456 165
200 456 170
200 456 180
200 456 190

ST-558



1/4" IG. 300 - 500 bar. Max. 90 °C

R+M Nr.	D	C
200 558 540	04	braun
200 558 550	05	schwarz
200 558 560	06	rot



Kit ST-558

R+M Nr.
200 558 140
200 558 150
200 558 160

ST-458.1



1/4" IG. Spritzwinkel 20°.
120 - 250 bar. Max. 100 °C

R+M Nr.	D	C
200 458 811	11	
200 458 812	12	
200 458 813	13	
200 458 815	15	
200 458 818	18	
200 458 820	20	
200 458 825	25	
200 458 830	30	



Kit ST-458.1

R+M Nr.
200 458 311
200 458 312
200 458 313
200 458 315
200 458 318
200 458 320
200 458 325
200 458 330



1/2" IG. Spritzwinkel 20°.
120 - 250 bar. Max. 100 °C

R+M Nr.	D	C
200 458 745	045	hellgrün
200 458 755	055	hellblau
200 458 770	07	rosa
200 458 791	09	grün
200 458 712	12	
200 458 715	15	
200 458 720	20	
200 458 730	30	



Kit ST-458.1

R+M Nr.
200 458 245
200 458 255
200 458 270
200 458 290
200 458 312
200 458 315
200 458 320
200 458 330

Suttner Rotordüsen mit Hartmetalleinsatz

ST-559



1/4" IG. 300-600 bar. Max. 90 °C

R+M Nr.	D
200 559 520	02
200 559 530	03
200 559 540	04
200 559 550	05
200 559 555	055
200 559 560	06



M20x1 IG. 300-600 bar. Max. 90 °C

R+M Nr.	D
200 559 320	02
200 559 330	03
200 559 340	04



Kit ST-559

R+M Nr.
200 559 120
200 559 130
200 559 140
200 559 150
200 559 155
200 559 160