

Vario nozzles and triple nozzles

Triple nozzles



M22 M. Lance with triple nozzle. Max. 250 bar / 80 °C

R+M Nr.	D	C	↔	M*
657 545 03	045	blue	430 mm	zinc-plated steel
657 555 03	055	red	430 mm	zinc-plated steel
657 560 03	06	green	430 mm	zinc-plated steel

R+M Nr.



1/4" F. Housing black. Max. 250 bar / 80 °C

R+M Nr.	D	C
657 545	045	blue
657 555	055	red
657 560	06	green

M18 F. Housing black. Max. 250 bar / 80 °C

R+M Nr.	D	C
657 545 1	045	blue
657 555 1	055	red
657 560 1	06	green

Functional principle triple nozzles



Adjustable nozzles



M22 M. Lance with adjustable nozzle. Spray angle 25°. Max. 200 bar / 150 °C

R+M Nr.	D	↔	M*
657 340 30	04	430 mm	zinc-plated steel
657 345 30	045	430 mm	zinc-plated steel
657 350 30	05	430 mm	zinc-plated steel
657 355 30	055	430 mm	zinc-plated steel
657 370 30	07	430 mm	zinc-plated steel

R+M Nr.	D	↔	M*
657 340 309	04	430 mm	stainless steel
657 345 309	045	430 mm	stainless steel
657 350 309	05	430 mm	stainless steel
657 355 309	055	430 mm	stainless steel
657 370 309	07	430 mm	stainless steel



Plug KW. Lance with adjustable nozzle. Without nozzle. Max. 200 bar / 150 °C

R+M Nr.	↔	M*
657 300 7	600 mm	zinc-plated steel

R+M Nr.	↔	M*
657 300 79	600 mm	stainless steel

* lance