

Suttner rotating nozzles with ceramic insert



A Kr

Plug KW. Lance with vented handle ST-9 380 mm and rotating nozzle ST-458.1. Spray angle 20°. 200 - 400 bar. Max. 100 °C

Plug KW. Lance with vented handle ST-9 380 mm and rotating nozzle ST-458.1. Spray angle 20°. 200 - 400 bar. Max. 100 °C

R+M Nr.	D	C	↔	M*
653 835 014	035	purple	1,000 mm	zinc-plated steel
653 840 014	04	brown	1,000 mm	zinc-plated steel
653 845 014	045	light green	1,000 mm	zinc-plated steel
653 850 014	05	black	1,000 mm	zinc-plated steel
653 855 014	055	light blue	1,000 mm	zinc-plated steel
653 860 014	06	red	1,000 mm	zinc-plated steel
653 865 014	065	nature	1,000 mm	zinc-plated steel
653 870 014	07	pink	1,000 mm	zinc-plated steel
653 880 014	08	orange	1,000 mm	zinc-plated steel

R+M Nr.	D	C	↔	M*
653 835 023	035	purple	1,000 mm	stainless steel
653 840 023	04	brown	1,000 mm	stainless steel
653 845 023	045	light green	1,000 mm	stainless steel
653 850 023	05	black	1,000 mm	stainless steel
653 855 023	055	light blue	1,000 mm	stainless steel
653 860 023	06	red	1,000 mm	stainless steel
653 865 023	065	nature	1,000 mm	stainless steel
653 870 023	07	pink	1,000 mm	stainless steel
653 880 023	08	orange	1,000 mm	stainless steel

Cleantecs rotating nozzles with carbide insert

HM 500



Kit
HM 500



K

G9/16". Spray angle 20°. Max. 500 bar / 90 °C

R+M Nr.	D
655 500 630	03

R+M Nr.
655 500 130

HM 500



Kit
HM 500



K

M20x1. Spray angle 20°. Max. 500 bar / 90 °C

R+M Nr.	D
655 500 640	028

R+M Nr.
655 500 130

HM 500



Kit
HM 500



K

M20x1. Spray angle 20°. Max. 500 bar / 90 °C

R+M Nr.	D
655 500 650	05

R+M Nr.
655 500 150

HM 500



Kit
HM 500



K

1/4" F. Spray angle 20°. Max. 500 bar / 90 °C

R+M Nr.	D
655 500 520	02
655 500 525	025
655 500 530	03
655 500 535	035
655 500 540	04
655 500 545	045
655 500 550	05
655 500 555	055
655 500 560	06
655 500 570	07

R+M Nr.
655 500 120
655 500 125
655 500 130
655 500 135
655 500 140
655 500 145
655 500 150
655 500 155
655 500 160
655 500 170

HM 700



Kit
HM 700



K

1/4" F. Spray angle 20°. Max. 700 bar / 90 °C. Delivery time of approx. 1 week

R+M Nr.	D
655 700 520	02
655 700 525	025
655 700 530	03
655 700 535	035
655 700 540	04
655 700 545	045
655 700 550	05
655 700 555	055
655 700 560	06
655 700 570	07

R+M Nr.
655 700 120
655 700 125
655 700 130
655 700 135
655 700 140
655 700 145
655 700 150
655 700 155
655 700 160
655 700 170

HM 1000



Kit
HM 1000



K

1/4" F. Spray angle 20°. Max. 1,000 bar / 90 °C. Delivery time of approx. 1 week

R+M Nr.	D
655 100 520	02
655 100 525	025
655 100 530	03
655 100 535	035
655 100 540	04
655 100 545	045
655 100 550	05
655 100 555	055
655 100 560	06
655 100 570	07

R+M Nr.
655 100 120
655 100 125
655 100 130
655 100 135
655 100 140
655 100 145
655 100 150
655 100 155
655 100 160
655 100 170

* lance

Symbols **D** nozzle **C** colour coding **↔** length **M** material