

Rotating nozzles

R+M 150



K

Plug K. Lance with rotating nozzle R+M 150. Spray angle 17°. 50 - 150 bar. Max. 60 °C

R+M Nr.	D	C	⇄	M*	R+M Nr.
653 325 011	025	green	430 mm	zinc-plated steel	
653 330 011	03	yellow	430 mm	zinc-plated steel	
653 335 011	035	black	430 mm	zinc-plated steel	
653 340 011	04	blue	430 mm	zinc-plated steel	
653 345 011	045	dark green	430 mm	zinc-plated steel	



A

Plug KW. Lance with rotating nozzle R+M 150. Spray angle 17°. 50 - 150 bar. Max. 60 °C

R+M Nr.	D	C	⇄	M*	R+M Nr.
653 325 05	025	green	430 mm	zinc-plated steel	
653 330 05	03	yellow	430 mm	zinc-plated steel	
653 335 05	035	black	430 mm	zinc-plated steel	
653 340 05	04	blue	430 mm	zinc-plated steel	
653 345 05	045	dark green	430 mm	zinc-plated steel	



Kr

M22 M. Lance with rotating nozzle R+M 150. Spray angle 17°. 50 - 150 bar. Max. 60 °C

R+M Nr.	D	C	⇄	M*	R+M Nr.
653 325 03	025	green	430 mm	zinc-plated steel	
653 330 03	03	yellow	430 mm	zinc-plated steel	
653 335 03	035	black	430 mm	zinc-plated steel	
653 340 03	04	blue	430 mm	zinc-plated steel	
653 345 03	045	dark green	430 mm	zinc-plated steel	

* lance

Symbols **D** nozzle **C** colour coding **⇄** length **M** material **DN** nominal diameter **⇄** flow