

Water intake filters

R+M filter



Aluminium. Complete with screen (stainless steel). 300 microns. Max. 10 bar / 60 l/min / 80 °C

R+M Nr.	⊙	⊖	↔	⊓
730 504	1/2" F	1/2" M	83	34

ST-33



Screen. Stainless steel

R+M Nr.	microns
730 504 03	300



Complete with screen (stainless steel). 400 micron. Max. 10 bar / 60 l/min / 60 °C

R+M Nr.	⊙	⊖	↔	⊓
200 033 540	1/2" F	1/2" M	69	38



Screen. Stainless steel

R+M Nr.	microns
120 000 765	400

ST-33



Complete with filter fine core washable (stainless steel and plastic). ⊓ 95 mm
⊓ 112 mm. Max. 6 bar / 60 °C / 50 l/min

R+M Nr.	⊙	⊖	microns
200 033 700	3/4" F	3/4" M	50
200 033 705	1/2" F	1/2" M	125



Filter fine core washable. Stainless steel + plastic

R+M Nr.	microns
020 001 735	50
020 001 737	125



Complete with filter fine core washable (stainless steel and plastic). 50 microns. Max. 6 bar / 60 °C / 50 l/min

R+M Nr.	⊙	⊖	⊓
200 033 900	3/4" F	3/4" M	141



Filter fine core washable. Stainless steel + plastic

R+M Nr.	microns
020 000 670	50

Water filter 3"



Complete with screen (plastic). 60 microns. Max. 10 bar / 50 l/min / 50 °C

R+M Nr.	⊙	⊖	⊓
734 40	3/4" M	3/4" F	123



Screen. Plastic. 60 microns

R+M Nr.
734 703

Y-filter



Complete with screen (stainless steel). 500 micron. Max. 10 bar / 60 l/min / 60 °C


R+M Nr.	⊙	⊖	⊓
732 038	3/8" F	3/8" F	58
732 012	1/2" F	1/2" F	58
732 034	3/4" F	3/4" F	70

Filter DN 17



Complete with screen. With integrated shut-off valve for the flow of water. * 250 microns. Max. 10 bar / 120 l/min / 90 °C

R+M Nr.	⊙	⊖	↔
732 923 00	3/4" M	3/4" F	123



Filter fine core washable. Stainless steel + plastic. 250 microns

R+M Nr.
732 005 945

* A pre-shut-off is not necessary.

The higher the number of microns the more coarsely meshed are the meshes: 500 microns = coarse . 50 microns = fine

Symbols ⊙ inner diameter ⊕ inlet ⊖ outlet ↔ length ⊓ height TYP type ⊙ thread ⊓ volume ↔ flow