

Protège-buses et porte-buses

Porte-buses hydroblade®



1/4" F : M20 M.
Porte-buse.
Inox

R+M Nr.
200 088 125



M20x1 F.
Protège-buse.
Laiton

R+M Nr.
020 000 085

Manchons de pistolet



1/4" M. Manchon ST-28 Cool & Compact.
Max. 400 bar / 150 °C

R+M Nr.	☺	ISO	↔	M
200 028 303	1/4" M	300 mm	330 mm	acier zingué



1/4" M. Manchon ST-29 Cool & Compact.
Max. 400 bar / 150 °C

R+M Nr.	☺	ISO	↔	M
200 029 303	1/4" M	300 mm	330 mm	inox



1/4" M. Manchons avec coquilles ST-9.1 et raccord manuel M22.
Max. 400 bar / 150 °C

R+M Nr.	☺	↔	M
200 009 730	M22 F	350 mm	inox
200 009 731	M22 F	350 mm	acier zingué



1/4" M. Manchon avec coquilles ST-9.1 et coupleur femelle KW.
Max. 400 bar / 150 °C

R+M Nr.	☺	↔	M
200 009 750	coupleur KW	260 mm	inox



1/4" M. Manchon surmoulé et raccord manuel M22.
Max. 400 bar / 150 °C

R+M Nr.	☺	↔	M
202 300 400	M22 F	340 mm	acier zingué



1/4" M. Manchon avec isolation ST-9.9-19 330 mm et raccord manuel M22.
Max. 400 bar / 150 °C

R+M Nr.	☺	↔	M
200 009 945	M22 F	370 mm	acier zingué



1/4" M. Manchon avec isolation ST-9.9-22 330 mm et raccord manuel M22.
Max. 400 bar / 150 °C

R+M Nr.	☺	↔	M
200 009 940	M22 F	370 mm	acier zingué



1/4" M. Manchon surmoulé.
Max. 400 bar / 150 °C

R+M Nr.	☺	ISO	↔	M
070 004 340	1/4" M	400 mm	440 mm	inox



1/4" M. Manchons surmoulés.
Max. 400 bar / 150 °C

R+M Nr.	☺	ISO	↔	M
070 000 330	1/4" M	300 mm	330 mm	acier zingué
070 000 240	1/4" M	400 mm	440 mm	acier zingué



1/4" M. Manchon surmoulé.
Max. 400 bar / 150 °C

R+M Nr.	☺	ISO	↔	M
070 003 229	1/4" M	300 mm	330 mm	inox