

Quick connect spray nozzles by Spraying Systems

limited stock

- » Original Spraying Systems nozzles exclusively for R+M / Suttner
- » High strength plastic. Highly impact resistant.
- » Long lifetime and excellently thermal and chemical stability. Resistant to mineral acids and alkaline solutions.
- » Nipple stainless steel. Nipple at black nozzle plastic.
- » Suitable for applications requiring a frequent and quick change of the spraying angle.
- » Max. 210 bar



Blasting nozzle. Delivers a very concentrated stream of water. **Care should be used to avoid gouging wood or damaging fragile surfaces.**

Chiseling nozzle. The spray should be directed at a 45° angle to the surface and used like a scraper to remove paint, grease and dirt.

Flushing nozzle. Best suited for flushing dirt, mud and grime.

Wash nozzle. Recommended for rinsing and moderate washing.

Low pressure soap nozzle. Designed for pre-spraying detergents on all kinds of surfaces. Low pressure rinsing.

	0°	15°	25°	40°	65°
ⓓ	R+M Nr.	R+M Nr.	R+M Nr.	R+M Nr.	R+M Nr.
03	610 107	613 107			
035	610 207	613 207	617 807	621 207	
04	610 307	613 307	617 907	621 307	
045	610 407	613 407	618 007	621 407	
40					626 807

Quick connect spray nozzles with hardened stainless steel insert

limited stock

- » High strength plastic. Highly impact resistant
- » Long lifetime and excellently thermal stability.
- » Nipple stainless steel. Nipple at black nozzle made out of brass.
- » Suitable for applications requiring a frequent and quick change of the spraying angle.
- » Max. 210 bar



	0°	15°	25°	40°
ⓓ	R+M Nr.	R+M Nr.	R+M Nr.	R+M Nr.
035		613 208		
045	610 408	613 408	618 008	
05	610 508		618 108	621 508
055	610 608	613 608	618 208	621 608
06		613 708	618 308	

Accessories quick connect spray nozzles



Coupling 1/4" F NPT

Nipple 1/4" M NPT

Nozzle holder for quick connect spray nozzles. Suitable for 1/4" lances. Without accessories

R+M Nr.	R+M Nr.	R+M Nr.
550 001 40	550 011 40	020 002 510