

**turbodevil - our new turbodevil floor cleaner series**

**turbodevil – BASIC**

- » Especially designed for professional cleaning applications
- » **Max. 60 °C. 1000 r.p.m. at 3 - 60 °C**
- » Completely stainless design
- » Heat-resistant all around protection ensures a safe handling by protection against splashes and stones
- » The precision rotor arm is counterbalanced, precisely equilibrated and welded by robots
- » Low vibration and reliable running

- » Suitable for applications up to about 150 annual operation hours are guaranteed



**Surface cleaner TD 300 BASIC**



Surface cleaner with a newly developed swivel with pivoting inlet for high revolutions per minute. The bending of the swivel is variably adjustable thus making an easy cleaning of floors and walls possible. 3 industrial castors (60 mm). 2 nozzles 1/4" M are required. Max. 1800 l/h / 60 °C

| R+M Nr.     | ∅      | ⓐ      | Ⓟ            |
|-------------|--------|--------|--------------|
| 521 030 300 | 300 mm | 1/4" F | max. 275 bar |



**Newly developed:**  
Swivel for high revolutions with pivoting inlet




**3 or 4 industrial castors (60 mm):**  
Easy and flexible steering



**Precision rotor:**  
Welded by robots

**Surface cleaner TD 410 BASIC**



| R+M Nr.     | ∅      | ⓐ      | Ⓟ            |
|-------------|--------|--------|--------------|
| 521 042 300 | 410 mm | 1/4" F | max. 275 bar |

**Surface cleaner TD 520 BASIC**



**Swivel:**  
With triple bearing system



ST-2600  
**LTF**


We recommend using the gun ST-2600 with patented LTF technology.

**Accessories for TD 300 & TD 410 & TD 410 INDUSTRIAL**



Lance ST-007. 1/4" M : Plug KW. Stainless steel 1000 mm

| R+M Nr.    |
|------------|
| 512 495 90 |



Lance extension. 1/4" M : M22 M. Stainless steel 500 mm

| R+M Nr. |
|---------|
| 513 129 |



Adapter. 1/4" M : M18 F. Stainless steel

| R+M Nr. |
|---------|
| 519 70  |

**To optimally adapt the surface cleaner to the high pressure cleaner, nozzles are excluded.**

**Nozzles with 1/4" M same size are required.**

**All surface cleaner are packed separately.**

Surface cleaner with foldable handle bar for space saving and reasonable transport. Swivel with triple bearing system. 4 industrial castors (60 mm). 2 nozzles 1/4" M are required. Max. 2400 l/h / 60 °C

| R+M Nr.     | ∅      | ⓐ       | Ⓟ            | incl.          |
|-------------|--------|---------|--------------|----------------|
| 521 052 300 | 520 mm | 1/4" F  | max. 275 bar | -              |
| 521 052 301 | 520 mm | 3/8" F  | max. 275 bar | ST-2600        |
| 521 052 304 | 520 mm | 3/8" F  | max. 275 bar | ST-2600 swivel |
| 521 052 302 | 520 mm | M22 F   | max. 275 bar | -              |
| 521 052 303 | 520 mm | Plug KW | max. 275 bar | -              |

**Symbols** ⓐ inlet Ⓟ pressure ∅ diameter