

## Coupling-system ST-245

### Nipple ST-245



⊖ 1/4" M.  
Stainless steel.  
Max. 350 bar

R+M Nr.	⊖
040 005 447	27.5



⊖ 1/4" M.  
Stainless steel.  
Max. 350 bar

R+M Nr.	⊖
040 005 446	33.5



⊖ 1/4" M. Stainless steel. Max. 350 bar.  
For wear cone

R+M Nr.	⊖
040 005 445	3 42.0

### ST-245 Coupling / wear cone ST-245




R+M Nr.	⊖
200 245 500	1 1/4" F



R+M Nr.	⊖
200 245 510	1 3/8" M

For 040 005 445



R+M Nr.	⊖
040 005 431	2



4  
Suitable for all 1/4" F nozzles for sewer cleaning.

## Mud suckers

### The high-performance mud sucker for all standard pressure washers

extracts stones (up to 20 mm), mud, dirt, sand, algae & sediment.  
Operating pressure min. 80 bar at 7 l/min. Suction power of approx. 8,000 to 18,000 l/h. Spiral hose: DN 38 mm, length 5 m



M22 M

M21 M

1/2" M

M18 M

Plug KW

⊖	R+M Nr.	R+M Nr.	R+M Nr.	R+M Nr.
04	545 504 0	545 514 0	545 524 0	545 534 0
045	545 504 5	545 514 5	545 524 5	545 534 5
05	545 505 0	545 515 0	545 525 0	545 535 0
055	545 505 5	545 515 5	545 525 5	545 535 5
06	545 506 0	545 516 0	545 526 0	545 536 0
065	545 506 5	545 516 5	545 526 5	545 536 5
07	545 507 0	545 517 0	545 527 0	545 537 0
08	545 508 0	545 518 0	545 528 0	545 538 0
10	545 501 0			

R+M Nr.	⊖	HP hose ⊖
545 545 5	055	5 m
545 546 0	06	5 m

### Performance chart

high pressure cleaner		capacity of mud sucker	
⊖	⊖	capacity	capacity
100 bar	10 l/min	ca. 170 l/min	ca. 10,000 l/h
150 bar	12 l/min	ca. 220 l/min	ca. 13,000 l/h
200 bar	15 l/min	ca. 300 l/min	ca. 18,000 l/h

Symbols ⊖ pressure ⊖ flow ⊖ nozzle ⊖ inlet ⊖ length