

Suttner Rotordüsen mit Keramikeinsatz



A Kr

Stecknippel KW. Strahlrohr mit Isolierung ST-9 380 mm und Rotordüse ST-458.1. Spritzwinkel 20°. 200 - 400 bar. Max. 100 °C

| R+M Nr. | D | ↔ | M* |
|-------------|-----|----------|----------------|
| 653 835 014 | 035 | 1.000 mm | Stahl verzinkt |
| 653 840 014 | 04 | 1.000 mm | Stahl verzinkt |
| 653 845 014 | 045 | 1.000 mm | Stahl verzinkt |
| 653 850 014 | 05 | 1.000 mm | Stahl verzinkt |
| 653 855 014 | 055 | 1.000 mm | Stahl verzinkt |
| 653 860 014 | 06 | 1.000 mm | Stahl verzinkt |
| 653 865 014 | 065 | 1.000 mm | Stahl verzinkt |
| 653 870 014 | 07 | 1.000 mm | Stahl verzinkt |
| 653 880 014 | 08 | 1.000 mm | Stahl verzinkt |

Stecknippel KW. Strahlrohr mit Isolierung ST-9 380 mm und Rotordüse ST-458.1. Spritzwinkel 20°. 200 - 400 bar. Max. 100 °C

| R+M Nr. | D | ↔ | M* |
|-------------|-----|----------|-----------|
| 653 835 023 | 035 | 1.000 mm | Edelstahl |
| 653 840 023 | 04 | 1.000 mm | Edelstahl |
| 653 845 023 | 045 | 1.000 mm | Edelstahl |
| 653 850 023 | 05 | 1.000 mm | Edelstahl |
| 653 855 023 | 055 | 1.000 mm | Edelstahl |
| 653 860 023 | 06 | 1.000 mm | Edelstahl |
| 653 865 023 | 065 | 1.000 mm | Edelstahl |
| 653 870 023 | 07 | 1.000 mm | Edelstahl |
| 653 880 023 | 08 | 1.000 mm | Edelstahl |

Cleantecs Rotordüsen mit Hartmetalleinsatz

HM 500



K

Kit
HM 500



G9/16". Spritzwinkel 20°. Max. 500 bar / 90 °C

| R+M Nr. | D |
|-------------|----|
| 655 500 630 | 03 |

| R+M Nr. |
|-------------|
| 655 500 130 |

HM 500



K

Kit
HM 500



M20x1. Spritzwinkel 20°. Max. 500 bar / 90 °C

| R+M Nr. | D |
|-------------|-----|
| 655 500 640 | 028 |

| R+M Nr. |
|-------------|
| 655 500 130 |

HM 500



K

Kit
HM 500



M20x1. Spritzwinkel 20°. Max. 500 bar / 90 °C

| R+M Nr. | D |
|-------------|----|
| 655 500 650 | 05 |

| R+M Nr. |
|-------------|
| 655 500 150 |

HM 500



1/4" IG. Spritzwinkel 20°. Max. 500 bar / 90 °C

| R+M Nr. | D |
|-------------|-----|
| 655 500 520 | 02 |
| 655 500 525 | 025 |
| 655 500 530 | 03 |
| 655 500 535 | 035 |
| 655 500 540 | 04 |
| 655 500 545 | 045 |
| 655 500 550 | 05 |
| 655 500 555 | 055 |
| 655 500 560 | 06 |
| 655 500 570 | 07 |

Kit
HM 500



| R+M Nr. |
|-------------|
| 655 500 120 |
| 655 500 125 |
| 655 500 130 |
| 655 500 135 |
| 655 500 140 |
| 655 500 145 |
| 655 500 150 |
| 655 500 155 |
| 655 500 160 |
| 655 500 170 |

HM 700



1/4" IG. Spritzwinkel 20°. Max. 700 bar / 90 °C. Lieferzeit ca. 1 Woche

| R+M Nr. | D |
|-------------|-----|
| 655 700 520 | 02 |
| 655 700 525 | 025 |
| 655 700 530 | 03 |
| 655 700 535 | 035 |
| 655 700 540 | 04 |
| 655 700 545 | 045 |
| 655 700 550 | 05 |
| 655 700 555 | 055 |
| 655 700 560 | 06 |
| 655 700 570 | 07 |

Kit
HM 700



| R+M Nr. |
|-------------|
| 655 700 120 |
| 655 700 125 |
| 655 700 130 |
| 655 700 135 |
| 655 700 140 |
| 655 700 145 |
| 655 700 150 |
| 655 700 155 |
| 655 700 160 |
| 655 700 170 |

HM 1000



1/4" IG. Spritzwinkel 20°. Max. 1.000 bar / 90 °C. Lieferzeit ca. 1 Woche

| R+M Nr. | D |
|-------------|-----|
| 655 100 520 | 02 |
| 655 100 525 | 025 |
| 655 100 530 | 03 |
| 655 100 535 | 035 |
| 655 100 540 | 04 |
| 655 100 545 | 045 |
| 655 100 550 | 05 |
| 655 100 555 | 055 |
| 655 100 560 | 06 |
| 655 100 570 | 07 |

Kit
HM 1000



| R+M Nr. |
|-------------|
| 655 100 120 |
| 655 100 125 |
| 655 100 130 |
| 655 100 135 |
| 655 100 140 |
| 655 100 145 |
| 655 100 150 |
| 655 100 155 |
| 655 100 160 |
| 655 100 170 |

* Strahlrohr

Symbole D Düse ↔ Länge M Material