

High pressure telescopic lances

- » Light and handy. Length easily adjustable. Adjustable from 2.3 m to 7.4 m.
- » Lance with embedded high pressure hose and mounted Suttner gun ST-601. Lance without high pressure nozzle.
- » Max. 275 bar / 100 °C

Our telescopic high pressure lances are up to 30 % lighter than comparable lances.



R+M Nr.	⌀	↻	↔	Ⓒ
525 070 8	2.4 kg	1/4" M	2.3 - 3.8 m	3/8" F
525 085 8	4.3 kg	1/4" M	2.3 - 5.6 m	3/8" F
525 100 8	5.4 kg	1/4" M	2.9 - 7.4 m	3/8" F



K

R+M Nr.	⌀	↻	↔	Ⓒ
525 070 1	2.6 kg	nozzle protector without tip	2.3 - 3.8 m	M22 M
525 085 1	4.5 kg	nozzle protector without tip	2.3 - 5.6 m	M22 M
525 100 1	5.6 kg	nozzle protector without tip	2.9 - 7.4 m	M22 M



R+M Nr.	⌀	↻	↔	Ⓒ
525 070 2	2.6 kg	nozzle protector ST-10 - 1/4" F NPT	2.3 - 3.8 m	3/8" F
525 085 2	4.5 kg	nozzle protector ST-10 - 1/4" F NPT	2.3 - 5.6 m	3/8" F
525 100 2	5.6 kg	nozzle protector ST-10 - 1/4" F NPT	2.9 - 7.4 m	3/8" F

Wall cleaner

- » Rotating wall cleaner suitable for telescopic lances
- » Splash guard stainless steel with rubberlip or brush strips
- » Splash guard ⌀ 300 mm
- » Without nozzles. 2 nozzles 1/4" M with 15° spray angle are required
- » Max. 250 bar / 90 °C.


R+M Nr.	Ⓒ	TYP	⌀
521 032 251	M22 M	rubberlip	1.9 kg
521 032 254	M22 M	brush strips	1.9 kg
521 032 256	M18 F	K rubberlip	1.9 kg
521 032 255	M18 F	K brush strips	1.9 kg
521 032 258	1/4" F	rubberlip	1.9 kg
521 032 257	1/4" F	brush strips	1.9 kg



turbodevil



with brush strips



with rubberlip

new



Screw connections

R+M Nr.
525 901

Symbols Ⓒ inlet ↻ outlet TYP type ↔ length ⌀ weight