

Rotabuses avec siège céramique, Suttner

ST-357.1

1/4" F. Cône 20°. 100 - 250 bar.
Max. 100 °C

R+M Nr.	D
200 357 530	03
200 357 535	035
200 357 540	04
200 357 545	045
200 357 550	05
200 357 555	055
200 357 560	06
200 357 565	065
200 357 570	07
200 357 580	08
200 357 690	09
200 357 510	100

M18 F. Cône 20°. 100 - 250 bar.
Max. 100 °C

R+M Nr.	D
200 357 330	03
200 357 335	035
200 357 340	04
200 357 345	045
200 357 350	05
200 357 355	055
200 357 360	06
200 357 365	065
200 357 370	07
200 357 380	08
200 357 390	09
200 357 310	100

1/8" M. Cône 20°. 100 - 250 bar.
Max. 100 °C

R+M Nr.	D
200 357 430	03
200 357 435	035
200 357 440	04
200 357 445	045
200 357 450	05
200 357 455	055
200 357 460	06
200 357 465	065
200 357 470	07
200 357 480	08
200 357 490	09
200 357 410	100



Kit ST-357.1

Adaptateur TR20

TR20 F : 1/4" M.
Inox.
Max. 400 bar / 150° C

R+M Nr.
565 685 19

ST-458.1

1/4" F. Cône 20°. 200 - 400 bar.
Max. 100 °C

R+M Nr.	D
200 458 630	03
200 458 635	035
200 458 640	04
200 458 645	045
200 458 650	05
200 458 655	055
200 458 660	06
200 458 665	065
200 458 670	07
200 458 680	08
200 458 690	09
200 458 610	100

M18 F. Cône 20°. 200 - 400 bar.
Max. 100 °C

R+M Nr.	D
200 458 331	03
200 458 335	035
200 458 340	04
200 458 345	045
200 458 350	05
200 458 355	055
200 458 360	06
200 458 365	065
200 458 370	07
200 458 380	08
200 458 390	09
200 458 310	100

1/8" M. Cône 20°. 200 - 400 bar.
Max. 100 °C

R+M Nr.	D
200 458 430	03
200 458 435	035
200 458 440	04
200 458 445	045
200 458 450	05
200 458 455	055
200 458 460	06
200 458 465	065
200 458 470	07
200 458 480	08
200 458 490	09
200 458 410	100



Kit ST-458.1

Code couleurs pour rotabuses Suttner



03 jaune 035 violet 04 brun 045 vert clair 05 noir 055 bleu ciel 06 rouge 065 naturel 07 rose 08 orange 09 vert 10 gris

Symboles  buse