

turbodevil - our new turbodevil floor cleaner series

turbodevil – BASIC

- » Especially designed for professional cleaning applications
- » **Max. 60 °C. 1,000 r.p.m. at 3 - 60 °C**
- » Completely stainless design
- » Heat-resistant all around protection ensures a safe handling by protection against splashes and stones
- » The precision rotor arm is counterbalanced, precisely equilibrated and welded by robots
- » Low vibration and reliable running

- » Suitable for applications up to about 150 annual operation hours are guaranteed



Surface cleaner TD 300 BASIC



Surface cleaner with a newly developed swivel with pivoting inlet for high revolutions per minute. The bending of the swivel is variably adjustable thus making an easy cleaning of floors and walls possible. 3 industrial castors (60 mm). 2 nozzles 1/4" M are required. Max. 1,800 l/h / 60 °C

Surface cleaner TD 410 BASIC



R+M Nr.	∅	Ⓢ	P
521 030 300	300 mm	1/4" F	max. 275 bar

R+M Nr.	∅	Ⓢ	P
521 042 300	410 mm	1/4" F	max. 275 bar



Newly developed:
Swivel for high revolutions with pivoting inlet



3 or 4 industrial castors (60 mm):
Easy and flexible steering



Precision rotor:
Welded by robots

Surface cleaner TD 520 BASIC



Swivel:
With triple bearing system



ST-2600
LTF

We recommend using the gun ST-2600 with patented LTF technology.

Accessories for TD 300 & TD 410 & TD 410 INDUSTRIAL



Lance ST-007. 1/4" M : Plug KW. Stainless steel 1,000 mm

R+M Nr.
512 495 90

High pressure nozzles




Adapter. 1/4" M : M18 F. Stainless steel

1/4" M NPT, 15 °

R+M Nr.
519 70

Impact = 100 %

D	R+M Nr.
02	613 05
025	613 07
03	613 10
04	613 30
045	613 40
05	613 50



Lance extension. 1/4" M : M22 M. Stainless steel 500 mm

R+M Nr.
513 129

Surface cleaner with foldable handle bar for space saving and reasonable transport. Swivel with triple bearing system. 4 industrial castors (60 mm). 2 nozzles 1/4" M are required. Max. 2,400 l/h / 60 °C

R+M Nr.	∅	Ⓢ	P	incl.
521 052 300	520 mm	1/4" F	max. 275 bar	-
521 052 301	520 mm	3/8" F	max. 275 bar	ST-2600
521 052 304	520 mm	3/8" F	max. 275 bar	ST-2600 swivel
521 052 302	520 mm	M22 F	max. 275 bar	-
521 052 303	520 mm	Plug KW	max. 275 bar	-

Symbols Ⓢ inlet P pressure ∅ diameter D nozzle