

## Suttner high pressure quick couplings ST-3100

### Couplings and plug ST-3100



Coupling : F. Stainless steel.  
Max. 250 bar / 150 °C

R+M Nr.	Ø
203 100 466	44 mm
203 100 461	44 mm
203 100 460	44 mm

Ø	DN
1/4"	10
3/8"	12
1/2"	12



Coupling : F. Stainless steel.  
Max. 250 bar / 150 °C

R+M Nr.	Ø
203 100 456	50 mm
203 100 455	50 mm



Coupling : M. Stainless steel.  
60° cone. Max. 250 bar / 150 °C

R+M Nr.	Ø
203 100 474	50 mm
203 100 655	45 mm



Coupling : M. Stainless steel.  
60° cone. Max. 250 bar / 150 °C

R+M Nr.	Ø
203 100 652	53 mm
203 100 473	55 mm
203 100 656	54 mm

Ø	DN
1/4"	10
3/8"	12
1/2"	12



Plug : F. Stainless steel.  
Max. 250 bar / 150 °C

R+M Nr.	Ø
040 005 665	35 mm
040 005 667	41 mm
040 005 661	47 mm



Plug : M. Stainless steel. 60° cone.  
Max. 250 bar / 150 °C

R+M Nr.	Ø
040 005 668	47 mm
040 005 662	47 mm



Plug : F. Hardened stainless steel.  
Max. 250 bar / 150 °C

R+M Nr.	Ø
040 005 465	35 mm
040 005 467	41 mm
040 005 461	47 mm

Ø	DN
1/4"	10
3/8"	12
1/2"	12



Plug : M. Hardened stainless steel.  
60° cone. Max. 250 bar / 150 °C

R+M Nr.	Ø
040 005 459	47 mm
040 005 462	47 mm



Plug : F. Stainless steel. For moulded handles.  
Max. 250 bar / 150 °C

R+M Nr.	Ø
040 005 664	40 mm



Plug : F. Stainless steel + brass.  
Max. 250 bar / 150 °C

R+M Nr.	Ø
203 100 665	56 mm

Ø	DN
M22	10



Coupling : M. Stainless steel.  
Max. 250 bar / 150 °C

R+M Nr.	Ø
203 100 660	57 mm



O-ring, 18x2

R+M Nr.	VPE
551 502 43	1
791 821 00	100



O-ring, 15.1x2.7

R+M Nr.	VPE
551 502 42	1
791 512 710	100