

Filter housings without cartridge filter

Plastic Brass / plastic Stainless steel



2-pieces. With drain.
Female thread brass.
Max. 10 bar / 50 °C

R+M Nr.	★	⊙	fi	↑
734 50	■	3/4"	5"	188
734 60	■	1"	5"	188
734 70	■	3/4"	9.3/4"	310
734 80	■	1"	9.3/4"	310
734 820 034	■	3/4"	20"	583
734 820 001	■	1"	20"	583



3-pieces. With drain.
Female thread brass.
Max. 10 bar / 40 °C

R+M Nr.	★	⊙	fi	↑
734 290 03	■	3/4"	5"	207
734 290 11	■	1"	5"	207
734 290 04	■	3/4"	9.3/4"	337
734 290 05	■	1"	9.3/4"	337



3-pieces. With drain. Head nickel-plated brass. Filter cup plastic.
Max. 15 bar / 40 °C

R+M Nr.	★	⊙	fi	↑
734 330 2	■	1"	9.3/4"	315



3-pieces. With drain, key for housing and mounting bracket.
Max. 20 bar / 120 °C

R+M Nr.	★	⊙	fi	↑
734 304 1	■	1"	9.3/4"	350

Screen housings



Filter 2-pieces. Plastic. Max. 50 °C

R+M Nr.	★	(TYP)
734 504	■	small*
734 704	■	big*



Filter 3-pieces. Plastic. Max. 40 °C

R+M Nr.	★	(TYP)
734 200 13	■	small**
734 200 14	■	big**
734 330 21	■	big**

O-ring



R+M Nr.	★
734 506	■
734 510	■
734 200 70	■
734 304 11	■

Centering unit



R+M Nr.	★
734 210 36	■

Mounting brackets



Single. Zinc-plated steel

R+M Nr.	★
734 299 02	■



Single. Plastic

R+M Nr.	★
734 507	■



Double. Plastic

R+M Nr.	★
734 508	■

Keys for housing



For plastic head. For 2 pieces filter housing.

R+M Nr.	★
734 505	■



For brass head. For 3 pieces filter housing.

R+M Nr.	★
734 300 1	■
734 299 01	■

* with o-ring ** without o-ring