


Lances rotabuses avec siège en céramique, Suttner



A Kr

Coupleur KW. Lances tube zingué avec demi-coquilles ST-9 380 mm et rotabuse ST-458.1. Cône 20°. 200 - 400 bar. Max. 100 °C

R+M Nr.	D	↔	M)*
653 835 014	035	1.000 mm	acier zingué
653 840 014	04	1.000 mm	acier zingué
653 845 014	045	1.000 mm	acier zingué
653 850 014	05	1.000 mm	acier zingué
653 855 014	055	1.000 mm	acier zingué
653 860 014	06	1.000 mm	acier zingué
653 865 014	065	1.000 mm	acier zingué
653 870 014	07	1.000 mm	acier zingué
653 880 014	08	1.000 mm	acier zingué

Coupleur KW. Lances tube inox avec demi-coquilles ST-9 380 mm et rotabuse ST-458.1. Cône 20°. 200 - 400 bar. Max. 100 °C

R+M Nr.	D	↔	M)*
653 835 023	035	1.000 mm	inox
653 840 023	04	1.000 mm	inox
653 845 023	045	1.000 mm	inox
653 850 023	05	1.000 mm	inox
653 855 023	055	1.000 mm	inox
653 860 023	06	1.000 mm	inox
653 865 023	065	1.000 mm	inox
653 870 023	07	1.000 mm	inox
653 880 023	08	1.000 mm	inox

Rotabuses avec siège en métal durci, Cleantecs

HM 500



Kit HM 500



G9/16". Cône 20°.
Max. 500 bar / 90 °C

R+M Nr.	D
655 500 630	03

R+M Nr.
655 500 130

HM 500



Kit HM 500



M20x1. Cône 20°.
Max. 500 bar / 90 °C

R+M Nr.	D
655 500 640	028

R+M Nr.
655 500 130

HM 500



Kit HM 500



M20x1. Cône 20°.
Max. 500 bar / 90 °C

R+M Nr.	D
655 500 650	05

R+M Nr.
655 500 150

HM 500



Kit HM 500



1/4" F. Cône 20°.
Max. 500 bar / 90 °C

R+M Nr.	D
655 500 520	02
655 500 525	025
655 500 530	03
655 500 535	035
655 500 540	04
655 500 545	045
655 500 550	05
655 500 555	055
655 500 560	06
655 500 570	07

R+M Nr.
655 500 120
655 500 125
655 500 130
655 500 135
655 500 140
655 500 145
655 500 150
655 500 155
655 500 160
655 500 170

HM 700



Kit HM 700




1/4" F. Cône 20°.
Max. 700 bar / 90 °C.
Sur demande, délai 1 semaine

R+M Nr.	D
655 700 520	02
655 700 525	025
655 700 530	03
655 700 535	035
655 700 540	04
655 700 545	045
655 700 550	05
655 700 555	055
655 700 560	06
655 700 570	07

R+M Nr.
655 700 120
655 700 125
655 700 130
655 700 135
655 700 140
655 700 145
655 700 150
655 700 155
655 700 160
655 700 170

HM 1000



Kit HM 1000



1/4" F. Cône 20°.
Max. 1.000 bar / 90 °C.
Sur demande, délai 1 semaine

R+M Nr.	D
655 100 520	02
655 100 525	025
655 100 530	03
655 100 535	035
655 100 540	04
655 100 545	045
655 100 550	05
655 100 555	055
655 100 560	06
655 100 570	07

R+M Nr.
655 100 120
655 100 125
655 100 130
655 100 135
655 100 140
655 100 145
655 100 150
655 100 155
655 100 160
655 100 170

* Tube de lance