

weeddevil® – Our new device for weed control

- » Ideal for professional service provider in the garden-, municipal and building cleaning industry
- » Completely made out of stainless steel
- » For hot water use of up to 120 °C, 0 - 350 bar
- » Suitable for low and high pressure applications
- » A working width of 400 mm
- » 1/4" nozzles have the ideal spraying angle of 65°

» swivelling application on sloping and vertical areas is possible

Completely chemical-free!



weeddevil®



ST-2605

LTF

Our spray gun ST-2605 with the patented LTF technology is recommended for effortless working.



4 nozzles 1/4" M NPT are required

At the underside: concentrated and well-directed hot water without any temperature loss by an optimally designed housing having a perfect cleaning distance.



Useable at the left or right: the handle at the side optimises the handling and protects within hot water applications.

4 nozzles 1/4" M are required. 2 robustly industrial castors (260 mm). Max. 120 °C

R+M Nr.	M	castors ∅	working- ↔	C	⇌	P	°C	⊞	I / ↔
200 097 700	stainl. steel	260 mm	400 mm	1/4" F	4 x 1/4" F	max. 350 bar	120 °C	7.4 kg	1,250 / 530 mm

Accessories thermometer



Easy mounting with counter plate and screws (incl.), or with back spring

R+M Nr.	
200 097 420	

Accessories flow restrictor



Flow restrictor for water reduction. Incl. adapter and nozzles (1,0, 1,1, 1,2, 1,3, 1,4)

R+M Nr.	C	⇌
200 097 750	1/4" M	1/4" M / M22 F

Symbols **M** material **∅** diameter **C** inlet **⇌** outlet **↔** width **I** height **°C** temperature **⊞** weight