

Foam lances

ST-72.1 foam lances with air injector



1/4" M. Foam lance stainless steel with air injector, vented handle ST-9.9 330 mm, grip and stainless steel socket with nozzle. A foam injector is required. Max. 250 bar / 80 °C

R+M Nr.	D*	☰	C**	☰
200 072 633	2.0 mm	< 15 l/min	green	600 mm
200 072 625	2.3 mm	< 20 l/min	yellow	600 mm
200 072 627	2.7 mm	< 26 l/min	blue	600 mm
200 072 629	3.2 mm	> 26 l/min	red	600 mm

R+M Nr.	D*	☰	C**	☰
200 072 634	2.0 mm	< 15 l/min	green	1200 mm
200 072 626	2.3 mm	< 20 l/min	yellow	1200 mm
200 072 628	2.7 mm	< 26 l/min	blue	1200 mm
200 072 631	3.2 mm	> 26 l/min	red	1200 mm



M22 F. Foam lance stainless steel with air injector, vented handle ST-9.9 380 mm, grip and stainless steel socket with nozzle. A foam injector is required. Max. 250 bar / 80 °C

R+M Nr.	D*	☰	C**	☰
200 072 636	2.0 mm	< 15 l/min	green	600 mm
200 072 639	2.3 mm	< 20 l/min	yellow	600 mm
200 072 642	2.7 mm	< 26 l/min	blue	600 mm
200 072 644	3.2 mm	> 26 l/min	red	600 mm

R+M Nr.	D*	☰	C**	☰
200 072 637	2.0 mm	< 15 l/min	green	1200 mm
200 072 641	2.3 mm	< 20 l/min	yellow	1200 mm
200 072 643	2.7 mm	< 26 l/min	blue	1200 mm
200 072 645	3.2 mm	> 26 l/min	red	1200 mm



Plug KW. Foam lance stainless steel with air injector, vented handle ST-9.9 380 mm, grip and stainless steel socket with nozzle. A foam injector is required. Max. 250 bar / 80 °C

R+M Nr.	D*	☰	C**	☰
200 072 646	2.0 mm	< 15 l/min	green	600 mm
200 072 648	2.3 mm	< 20 l/min	yellow	600 mm
200 072 651	2.7 mm	< 26 l/min	blue	600 mm
200 072 653	3.2 mm	> 26 l/min	red	600 mm

R+M Nr.	D*	☰	C**	☰
200 072 647	2.0 mm	< 15 l/min	green	1200 mm
200 072 649	2.3 mm	< 20 l/min	yellow	1200 mm
200 072 652	2.7 mm	< 26 l/min	blue	1200 mm
200 072 654	3.2 mm	> 26 l/min	red	1200 mm

* air injector ** nozzle protector

Symbols ☰ length D nozzle ☰ flow C colour