

ST-175 Foam & Clean



K

Twin foam lance with vented handle ST-9 380 mm, change-over valve ST-58, ergonomic swivel screw coupling, nozzle protector without tip and foam head ST-75 without nozzle. A foam injector is required. Max. 350 bar / 45 l/min / 100 °C

R+M Nr.			
200 175 411	M22 F	-	420 mm

R+M Nr.



new

Twin foam lance with vented handle ST-9 205 mm, change-over valve ST-58, nozzle protector without tip and foam head ST-75 without nozzle. A foam injector is required. Max. 350 bar / 45 l/min / 100 °C

R+M Nr.			
200 175 412	1/4" F	-	420 mm

R+M Nr.



new

Twin foam lance with vented handle ST-9 205 mm, change-over valve ST-58, nozzle protector ST-10 without nozzle and foam head ST-75 without nozzle. A foam injector is required. Max. 350 bar / 45 l/min / 100 °C

R+M Nr.			
200 175 414	1/4" F	-	420 mm

R+M Nr.



new

Twin foam lance with vented handle ST-9 380 mm, change-over valve ST-58, nozzle protector ST-10 without nozzle and foam head ST-75 with nozzle 1.9. A foam injector is required. Max. 350 bar / 45 l/min / 100 °C

R+M Nr.			
200 175 430	M22 F	1.9	600 mm

R+M Nr.



new

Twin foam lance with vented handle ST-9 380 mm, change-over valve ST-58, nozzle protector ST-10 without nozzle and foam head ST-75 with nozzle 2.1. A foam injector is required. Max. 350 bar / 45 l/min / 100 °C

R+M Nr.			
200 175 431	M22 F	2.1	600 mm

R+M Nr.