

Suttner foam guns, ST-3225



Professional hp gun with progressive closing system and coupling ST-3100. Stainless steel. Field of application: foam and rinsing applications in the food industry etc. Industry standard. Max. 60 bar / 120 l/min / 100 °C

R+M Nr.	⊖	⊕
203 225 550	coupling ST-3100	1/2" F swivel



Professional hp gun with progressive closing system. Stainless steel. Field of application: foam and rinsing applications in the food industry etc. Industry standard. Max. 60 bar / 120 l/min / 100 °C

R+M Nr.	⊖	⊕
203 225 545	1/2" F	1/2" F swivel



Professional hp gun with coupling ST-3100. Stainless steel. Field of application: foam and rinsing applications in the food industry etc. Industry standard. Max. 60 bar / 120 l/min / 100 °C

R+M Nr.	⊖	⊕
203 225 540	coupling ST-3100	1/2" F swivel



Professional gun with progressive closing system, locking in opened position and coupling ST-3100. Stainless steel. Field of application: foam and rinsing applications in the food industry etc. Industry standard. Max. 24.5 bar / 120 l/min / 100 °C

R+M Nr.	⊖	⊕
203 225 650	coupling ST-3100	1/2" F swivel



Professional gun with progressive closing system and locking in opened position. Stainless steel. Field of application: foam and rinsing applications in the food industry etc. Industry standard. Max. 24.5 bar / 120 l/min / 100 °C

R+M Nr.	⊖	⊕
203 225 645	1/2" F	1/2" F swivel



Professional gun with locking in opened position and coupling ST-3100. Stainless steel. Field of application: foam and rinsing applications in the food industry etc. Industry standard. Max. 24.5 bar / 120 l/min / 100 °C

R+M Nr.	⊖	⊕
203 225 640	coupling ST-3100	1/2" F swivel

Foam lances

ST-74 foam lances with air injector



1/4" F. Foam lance stainless steel with air injector and stainless steel socket with nozzle 40° 150. Max. 90 °C

R+M Nr.	D	air injector	⊖	M	↔
200 074 505	2.1 mm	0.8 kg	stainless steel	530 mm	
200 074 500	2.3 mm	0.8 kg	stainless steel	530 mm	



Plug KW. Foam lance stainless steel with air injector and stainless steel socket with nozzle 40° 150. Max. 90 °C

R+M Nr.	D	air injector	⊖	M	↔
200 074 506	2.1 mm	0.8 kg	stainless steel	530 mm	
200 074 501	2.3 mm	0.8 kg	stainless steel	530 mm	

Foam lances ST-3100



Plug ST-3100. Foam lance stainless steel 300 mm with foam nozzle 50° 200

R+M Nr.	D	ISO	M	↔
203 100 630	50° 200	-	stainless steel	300 mm


Foam lances ST-3300



Plug ST-45. Foam lance stainless steel with nozzle protector and nozzle 50° 200

R+M Nr.	D	ISO	M	↔
203 300 300	nozzle 50° 200	-	stainless steel	255 mm

Nozzle protector ST-11



- » The nozzle protector ST-11 is suitable for nozzles 1/4" M.
- » Made out of plastics intended to come into contact with foodstuffs according to Regulation (EC) No. 1935/2004.
- » It is clamped undetachably between the nozzle and the nozzle sleeve.

R+M Nr.	C
020 001 124	white
020 001 149	blue
020 001 121	red
020 001 122	green

R+M Nr.	C
020 001 123	yellow
020 001 157	grey
020 001 158	black