

turbodevil - our new turbodevil floor cleaner series

turbodevil - agriculture cleaner Big Wheel

easyfarm365+



LTF

We recommend using the gun **easyfarm365+** with patented LTF technology.





Always at hand:
Lance holder for attachment at the fork



Lug:
The underside of the connecting tube remains on the handle



Space-saving:
Divisible fork



Large wheels:
For good grip



Carefully chosen:
With 30 mm well equipped for slatted floors



Extra robust:
Swivel with carbide sealings



Clean solution:
Extra thick rubber bristles for splashback






Surface cleaner with foldable handle bar Swivel with carbide sealings. Front-mounted castor (30 mm) ideal on slatted floors. 2 large big wheels. 2 nozzles 1/4" M are required. Max. 275 bar /1.800 l/h / 120 °C



R+M Nr.	∅	G	P
521 052 900	520 mm	1/4" IG	max. 275 bar


turbodevil - INDUSTRIAL

Surface cleaner TD 410 INDUSTRIAL



Newly developed:
Swivel for high revolutions with pivoting inlet





- » Especially designed for industrial cleaning applications
- » **For hot water use of up to 120 °C. 2.000 r.p.m. at 5 - 120 °C**
- » Heat-resistant all around protection ensures a safe handling by protection against splashes and stones
- » The precision rotor arm is counterbalanced, precisely equilibrated and welded by robots
- » Low vibration and reliable running are guaranteed
- » Suitable for applications of up to 500 annual operation hours
- » Use of a especially high quality, **3-ball bearing swivel joint with ceramic sealing elements** for high durability and extremely long stress
- » **Castors are made out of stainless steel**

Surface cleaner with a newly developed swivel with pivoting inlet for high revolutions per minute. The bending of the swivel is variably adjustable thus making an easy cleaning of floors and walls possible. 3 industrial castors (60 mm). 2 nozzles 1/4" M are required. Max. 1,800 l/h / 120 °C

R+M Nr.	∅	G	P
521 042 400	410 mm	1/4" F	max. 275 bar