

## Cartridge filter



Plastic cleanable. Reinforced version.  
Max. 40 °C

R+M Nr.	★	fi	microns	⌋
734 293 00	●●	5"	60	125
734 293 02	●●●●	9.3/4"	60	250
734 293 03	●●●●	9.3/4"	120	250



Plastic cleanable.  
Max. 40 °C

R+M Nr.	★	fi	microns	⌋
734 55	●	5"	60	128
734 54	●	5"	150	128
734 75	●●●	9.3/4"	60	250
734 74	●●●	9.3/4"	150	250



Cotton.  
Max. 40 °C

R+M Nr.	★	fi	microns	⌋
734 57	●	5"	5	128
734 56	●	5"	20	128
734 77	●●●●	9.3/4"	5	250
734 76	●●●●	9.3/4"	30	250
734 720 005	●	20"	5	510
734 720 025	●	20"	30	510



Stainless steel. Max. 120 °C

R+M Nr.	★	fi	microns	⌋
734 709 050	●●●●	9.3/4"	50	250



Iron remove filter

R+M Nr.	★	fi	⌋
734 709 060	●●●●	9.3/4"	250



Water softener. Polyphosphate

R+M Nr.	★	fi	⌋
734 58	●●	5"	125

The higher the number of microns the more coarsely meshed are the meshes: **500 microns = coarse** . **50 microns = fine**

Symbols ★ marking fi filter ○ thread ⌋ height TYP type