

PURClean365+® - food hose



PURClean365+® - Food hose according to (EG) 1935/2004, (EU) 10/2011 and (EG) 2023/2006. Designed for industrial foam applications

- » Field of application: foam hose and pre-spraying hose in the food industry. Suitable for contact with liquid food products
- » Suitable for water and water mixes of usual cleaning detergents

- » PVC hose with three layers and a smooth surface
- » Increased 1-layer rot-proof textile mesh.
- » About 20 % lighter and more flexible than comparable hose types

PURClean365+® 40

Female thread DKR

Male thread (AGR)

1/2" : 1/2"

-20 °C - 70 °C. Fittings stainless steel



R+M Nr.	↔
476 056 602 59	2.5 m
476 056 610 9	10.0 m
476 056 615 9	15.0 m
476 056 620 9	20.0 m
476 056 625 9	25.0 m
476 056 630 9	30.0 m
476 056 635 9	35.0 m
476 056 640 9	40.0 m

R+M Nr.	↔
476 046 602 59	2.5 m
476 046 610 9	10.0 m
476 046 615 9	15.0 m
476 046 620 9	20.0 m
476 046 625 9	25.0 m
476 046 630 9	30.0 m
476 046 635 9	35.0 m
476 046 640 9	40.0 m

PURClean365+® 40 per metre

R+M Nr.	DN	↔	⊗	P 20 °C	P 70 °C	BP 20 °C	⊞
303 660 40	12	10 - 100 m	4.5	100 bar	45 bar	≥ 250 bar	0.25 kg

PURClean365+® 100

Female thread DKR

Male thread (AGR)

1/2" : 1/2"

-20 °C - 100 °C. Fittings stainless steel



R+M Nr.	↔
477 056 602 59	2.5 m
477 056 610 9	10.0 m
477 056 615 9	15.0 m
477 056 620 9	20.0 m
477 056 625 9	25.0 m
477 056 630 9	30.0 m
477 056 635 9	35.0 m
477 056 640 9	40.0 m

R+M Nr.	↔
477 046 602 59	2.5 m
477 046 610 9	10.0 m
477 046 615 9	15.0 m
477 046 620 9	20.0 m
477 046 625 9	25.0 m
477 046 630 9	30.0 m
477 046 635 9	35.0 m
477 046 640 9	40.0 m

PURClean365+® 100 per metre

R+M Nr.	DN	↔	⊗	P 20 °C	P 100 °C	BP 20 °C	⊞
303 661 00	12	10 - 100 m	4.5	40 bar	18 bar	≥ 200 bar	0.25 kg

Symbols ↔ length DN nominal diameter P pressure ⊗ wall thickness BP burst pressure ⊞ outlet ⊞ inlet ISO insulation TYP type