

Foam lances

ST-72 foam lances with air injector



1/4" M. Foam lance stainless steel with air injector, vented handle ST-9 380 mm, grip and stainless steel socket with nozzle. A foam injector is required. Max. 250 bar / 80 °C

R+M Nr.	D*	☰	C**	☰
200 072 500	2.0 mm	< 15 l/min	green	600 mm
200 072 510	2.3 mm	< 20 l/min	yellow	600 mm
200 072 511***	2.7 mm	< 26 l/min	blue	600 mm
200 072 520	3.2 mm	> 26 l/min	red	600 mm

R+M Nr.	D*	☰	C**	☰
200 072 600***	2.0 mm	< 15 l/min	green	1200 mm
200 072 610	2.3 mm	< 20 l/min	yellow	1200 mm
200 072 620	3.2 mm	> 26 l/min	red	1200 mm



M22 F. Foam lance stainless steel with air injector, vented handle ST-9 380 mm, grip and stainless steel socket with nozzle. A foam injector is required. Max. 250 bar / 80 °C

R+M Nr.	D*	☰	C**	☰
200 072 504	2.0 mm	< 15 l/min	green	600 mm
200 072 514	2.3 mm	< 20 l/min	yellow	600 mm
200 072 524	3.2 mm	> 26 l/min	red	600 mm

R+M Nr.	D*	☰	C**	☰
200 072 614	2.3 mm	< 20 l/min	yellow	1,200 mm
200 072 624	3.2 mm	> 26 l/min	red	1,200 mm



Plug KW. Foam lance stainless steel with air injector, vented handle ST-9 380 mm, grip and stainless steel socket with nozzle. A foam injector is required. Max. 250 bar / 80 °C

R+M Nr.	D*	☰	C**	☰
200 072 502	2.0 mm	< 15 l/min	green	600 mm
200 072 512	2.3 mm	< 20 l/min	yellow	600 mm
200 072 522	3.2 mm	> 26 l/min	red	600 mm

R+M Nr.	D*	☰	C**	☰
200 072 612	2.3 mm	< 20 l/min	yellow	1,200 mm
200 072 622	3.2 mm	> 26 l/min	red	1,200 mm



1/4" M. Foam lance with air injector, vented handle ST-9 380 mm, grip and plastic socket with nozzle. A foam injector is required. Stainless steel and plastic intended to come into contact with foodstuffs according to Regulation 1935 / 2004 / EG. Max. 250 bar / 80 °C

R+M Nr.	D*	☰	C**	☰
200 072 635	2.3 mm	< 20 l/min	yellow	600 mm

R+M Nr.	D*	☰	C**	☰