

Foam head ST-75

By means of the foam head ST-75 different foam applications are possible as the air injector nozzle is easily exchangeable and adaptable. The flat spray nozzle can be infinitely adapted from the vertical position to the horizontal one. The maximum flow is dependent on the chosen nozzle size. By means of the integrated air injector in the foam head the air is sucked in on the face side. Independent of the length of the lance a constant foam quality is guaranteed. The spraying result is especially even as a high quality foam nozzle insert is used.  
Max. 350 bar / 100 °C



Stainless steel. ST-75 with nozzle.  
Max. 350 bar / 100 °C

R+M Nr.	∅*	⊕
200 075 514	1.60	1/4" F
200 075 515	1.90	1/4" F



Brass. ST-75 with nozzle.  
Max. 350 bar / 100 °C

R+M Nr.	∅*	⊕
200 075 574	1.20	1/4" F
200 075 576	1.35	1/4" F
200 075 577	1.45	1/4" F
200 075 572	1.60	1/4" F
200 075 575	1.75	1/4" F
200 075 573	1.90	1/4" F



Brass. ST-75 with nozzle.  
Max. 350 bar / 100 °C

R+M Nr.	∅*	⊕
200 075 554	1.20	1/4" F
200 075 552	1.60	1/4" F
200 075 553	1.90	1/4" F



Brass. ST-75 with nozzle.  
Max. 350 bar / 100 °C

R+M Nr.	∅*	⊕
200 075 562	1.60	1/4" F
200 075 563	1.90	1/4" F



Stainless steel. ST-75 with nozzle.  
Max. 350 bar / 100 °C

R+M Nr.	∅*	⊕
200 075 512	1.60	M18 F
200 075 513	1.90	M18 F



Brass. ST-75 with nozzle.  
Max. 350 bar / 100 °C

R+M Nr.	∅*	⊕
200 075 570	1.60	M18 F
200 075 571	1.90	M18 F



Brass. ST-75 with nozzle.  
Max. 350 bar / 100 °C

R+M Nr.	∅*	⊕
200 075 550	1.60	M18 F
200 075 551	1.90	M18 F



Brass. ST-75 with nozzle.  
Max. 350 bar / 100 °C

R+M Nr.	∅*	⊕
200 075 560	1.60	M18 F
200 075 561	1.90	M18 F



Air injector nozzle

R+M Nr.	∅*	D
200 075 401	1.05	03
200 075 402	1.10	035
200 075 403	1.20	04
200 075 405	1.35	05
200 075 425	1.40	055
200 075 406	1.45	06
200 075 427	1.55	07
200 075 407	1.60	075
200 075 408	1.70	08
200 075 410	1.90	10
200 075 413	2.10	13
200 075 415	2.30	15
200 075 420	2.65	20



Stainless steel. ST-75.1 with nozzle and without foam pad.  
Max. 350 bar / 100 °C

R+M Nr.	∅*	⊕
200 075 600	1.60	M18 F
200 075 601	1.90	M18 F



Brass. ST-75.1 without nozzle and without foam pad.  
Max. 350 bar / 80 °C

R+M Nr.	⊕
200 075 482	M 18 F
200 075 493	1/4" F



Brass. ST-75.1 without nozzle and without foam pad.  
Max. 350 bar / 80 °C

R+M Nr.	⊕
200 075 486	M18 F



Stainless steel. ST-75.1 with nozzle and without foam pad.  
Max. 350 bar / 100 °C

R+M Nr.	∅*	⊕
200 075 602	1.60	1/4" F
200 075 603	1.90	1/4" F



1/4" F : M18 M. Nozzle holder EG.

R+M Nr.	⊕
010 000 043	Brass
040 000 041	Stainless steel



O-ring. 10x2. Viton

R+M Nr.	VPE
790 20	1
790 201 00	100



Foam pad

R+M Nr.
540 500 09

\* hole diameter in mm  
\*\* nozzle size in mm