

Foam lances

Foam lance with insulated grip



ST-3100 connector. 280 mm foam lance made of stainless steel with 100 mm insulation and nozzle protection ST-11 with nozzle.
Max. 250 bar / 150 °C

R+M Nr.	D	ISO	M	↔
200 129 183	15° 20	100 mm	stainless steel	280 mm

Foam lance, bended with insulated grip



ST-3100 connector. 280 mm bended foam lance made of stainless steel with 100 mm insulation and nozzle protection ST-11 with nozzle.
Max. 250 bar / 150 °C

R+M Nr.	D	ISO	M	↔
200 129 184	15° 20	100 mm	stainless steel	280 mm

ST-74 foam lances with air injector



1/4" F. Foam lance stainless steel with air injector and stainless steel socket with nozzle 40° 150. Max. 90 °C

R+M Nr.	D air injector	⊗	M	↔
200 074 505	2.1 mm	0.8 kg	stainless steel	530 mm
200 074 500	2.3 mm	0.8 kg	stainless steel	530 mm


Foam lance ST-3100



Plug ST-3100. Foam lance stainless steel 300 mm with foam nozzle 50° 200

R+M Nr.	D	ISO	M	↔
203 100 630	50° 200	-	stainless steel	300 mm

Foam Nozzle Polypropylene




Max. 45 bar / 60 °C

R+M Nr.	D	⊗	Ⓢ	↔
203 100 920	50° 200	0.43 kg	plug ST-3100	75 mm
203 100 910	50° 200	0.42 kg	1/2" M	75 mm



Nozzle protector ST-11



- » The nozzle protector ST-11 is suitable for nozzles 1/4" M.
- » Made out of plastics intended to come into contact with foodstuffs according to Regulation (EC) No. 1935/2004.
- » It is clamped undetachably between the nozzle and the nozzle sleeve.

R+M Nr.	Ⓢ
020 001 124	white
020 001 149	blue
020 001 121	red
020 001 122	green

R+M Nr.	Ⓢ
020 001 123	yellow
020 001 157	grey
020 001 158	black