

Cartridge filter



Plastic cleanable. Reinforced version.
Max. 40 °C

| R+M Nr. | ★ | fi | microns | I |
|------------|---------|--------|---------|-----|
| 734 293 00 | ■ ■ | 5" | 60 | 125 |
| 734 293 02 | ■ ■ ■ ■ | 9.3/4" | 60 | 250 |
| 734 293 03 | ■ ■ ■ ■ | 9.3/4" | 120 | 250 |



Plastic cleanable.
Max. 40 °C

| R+M Nr. | ★ | fi | microns | I |
|---------|-------|--------|---------|-----|
| 734 55 | ■ | 5" | 60 | 128 |
| 734 54 | ■ | 5" | 150 | 128 |
| 734 75 | ■ ■ ■ | 9.3/4" | 60 | 250 |
| 734 74 | ■ ■ ■ | 9.3/4" | 150 | 250 |



Cotton.
Max. 40 °C

| R+M Nr. | ★ | fi | microns | I |
|---------|---------|--------|---------|-----|
| 734 57 | ■ | 5" | 5 | 128 |
| 734 56 | ■ | 5" | 20 | 128 |
| 734 77 | ■ ■ ■ ■ | 9.3/4" | 5 | 250 |
| 734 76 | ■ ■ ■ ■ | 9.3/4" | 20 | 250 |



Iron remove filter

| R+M Nr. | ★ | fi | ← | I |
|-------------|---------|--------|------|-----|
| 734 709 060 | ■ ■ ■ ■ | 9.3/4" | 0.85 | 250 |



Water softener. Polyphosphate

| R+M Nr. | ★ | fi | I |
|-------------|-----|-----|-----|
| 734 58 | ■ ■ | 5" | 125 |
| 734 820 035 | ■ | 20" | 510 |

The filters
734 58, 734 820 035 and
734 709 060
are not suitable for the
water supply of pumps.



Polypropylene. Max. 40 °C

| R+M Nr. | ★ | fi | microns | I |
|-------------|---|-----|---------|-----|
| 734 720 006 | ■ | 20" | 5 | 510 |
| 734 720 050 | ■ | 20" | 50 | 510 |



Stainless steel. Max. 120 °C

| R+M Nr. | ★ | fi | microns | I |
|-------------|---------|--------|---------|-----|
| 734 709 050 | ■ ■ ■ ■ | 9.3/4" | 50 | 250 |

The higher the number of microns the more coarsely meshed are the meshes: 500 microns = coarse . 50 microns = fine

Symbols ★ marking fi filter ○ thread I height TYP type