

### Foodjet - food hose with textile meshwork


**Foodjet** - High pressure hose according to DIN EN 854. Particularly resistant to animal and poultry fats

- » Field of application: cleaning hose designed for the poultry processing industry
- » Suitable for: oil, water, water-in-oil emulsion and water mixes with up to 50 % detergent

» Surface synthetic rubber. Particularly abrasion-, oil-, ozone-resistant and weatherproof.

- » Interior synthetic, oil-resistant rubber
- » 1 tight textile meshwork
- » **Max. 80 bar.** Burst pressure > 240 bar.
- 40 °C - +150 °C


#### Female thread DKR 1/2"



Fittings stainless steel

R+M Nr.	↔	↔
490 056 002 59	2.5 m	
490 056 010 9	10.0 m	
490 056 015 9	15.0 m	
490 056 020 9	20.0 m	
490 056 025 9	25.0 m	
490 056 030 9	30.0 m	
490 056 035 9	35.0 m	
490 056 040 9	40.0 m	

#### Male thread (AGR) 1/2"



Fittings stainless steel

R+M Nr.	↔	↔
490 046 002 59	2.5 m	
490 046 010 9	10.0 m	
490 046 015 9	15.0 m	
490 046 020 9	20.0 m	
490 046 025 9	25.0 m	
490 046 030 9	30.0 m	
490 046 035 9	35.0 m	
490 046 040 9	40.0 m	

#### Male thread (AGR) 1/2" : DKR 1/2"



Fittings stainless steel

R+M Nr.	↔	↔
490 057 002 59	2.5 m	
490 057 610 9	10.0 m	
490 057 615 9	15.0 m	
490 057 620 9	20.0 m	
490 057 625 9	25.0 m	
490 057 630 9	30.0 m	
490 057 635 9	35.0 m	
490 057 640 9	40.0 m	

#### Foodjet per metre

DN 12

R+M Nr.	↔	↔
303 60		10 - 95 m

### Foodjet 1500 - food hose with textile meshwork

**Foodjet 1500** - High pressure hose according to DIN EN 854. Particularly resistant to animal and poultry fats

- » Field of application: cleaning hose designed for the poultry processing industry
- » Suitable for: oil, water, water-in-oil emulsion and water mixes with up to 50 % detergent

» Surface synthetic rubber. Particularly abrasion-, oil-, ozone-resistant and weatherproof.

- » Interior synthetic, oil-resistant rubber
- » 1 tight textile meshwork
- » **Max. 125 bar.** Burst pressure > 375 bar.
- 40 °C - +150 °C


#### Female thread DKR 1/2"



Fittings stainless steel

R+M Nr.	↔	↔
490 445 660 259	2.5 m	
490 445 661 09	10.0 m	
490 445 661 59	15.0 m	
490 445 662 09	20.0 m	
490 445 662 59	25.0 m	
490 445 663 09	30.0 m	
490 445 663 59	35.0 m	
490 445 664 09	40.0 m	

#### Male thread (AGR) 1/2"



Fittings stainless steel

R+M Nr.	↔	↔
490 444 660 259	2.5 m	
490 444 661 09	10.0 m	
490 444 661 59	15.0 m	
490 444 662 09	20.0 m	
490 444 662 59	25.0 m	
490 444 663 09	30.0 m	
490 444 663 59	35.0 m	
490 444 664 09	40.0 m	

#### Male thread (AGR) 1/2" : DKR 1/2"



Fittings stainless steel

R+M Nr.	↔	↔
490 445 760 259	2.5 m	
490 445 761 09	10.0 m	
490 445 761 59	15.0 m	
490 445 762 09	20.0 m	
490 445 762 59	25.0 m	
490 445 763 09	30.0 m	
490 445 763 59	35.0 m	
490 445 764 09	40.0 m	

#### Foodjet 1500 per metre

DN 12

R+M Nr.	↔	↔
303 601 500		70 - 100 m

Fittings zinc-plated steel

R+M Nr.	↔	↔
490 445 660 25	2.5 m	
490 445 661 0	10.0 m	
490 445 661 5	15.0 m	
490 445 662 0	20.0 m	
490 445 662 5	25.0 m	
490 445 663 0	30.0 m	
490 445 663 5	35.0 m	
490 445 664 0	40.0 m	

Fittings zinc-plated steel

R+M Nr.	↔	↔
490 444 660 25	2.5 m	
490 444 661 0	10.0 m	
490 444 661 5	15.0 m	
490 444 662 0	20.0 m	
490 444 662 5	25.0 m	
490 444 663 0	30.0 m	
490 444 663 5	35.0 m	
490 444 664 0	40.0 m	

Fittings zinc-plated steel

R+M Nr.	↔	↔
490 445 760 25	2.5 m	
490 445 761 0	10.0 m	
490 445 761 5	15.0 m	
490 445 762 0	20.0 m	
490 445 762 5	25.0 m	
490 445 763 0	30.0 m	
490 445 763 5	35.0 m	
490 445 764 0	40.0 m	

Symbols ↔ length ⊕ inlet ⊖ outlet [ISO] insulation [M] material