

Cleantecs rotating nozzles with carbide insert

HM 500



Kit
HM 500



K

G9/16. Spray angle 20°. Max. 500 bar / 90 °C

R+M Nr.	D
655 500 630	03

HM 500



Kit
HM 500



K

M20x1. Spray angle 20°. Max. 500 bar / 90 °C

R+M Nr.	D
655 500 640	028

HM 500



Kit
HM 500



K

M20x1. Spray angle 20°. Max. 500 bar / 90 °C

R+M Nr.	D
655 500 650	05

R+M Nr.
655 500 150

HM 500



Kit
HM 500



1/4" F. Spray angle 20°. Max. 500 bar / 100 °C

R+M Nr.	D
655 500 520	02
655 500 525	025
655 500 530	03
655 500 535	035
655 500 540	04
655 500 545	045
655 500 550	05
655 500 555	055
655 500 560	06
655 500 570	07

HM 700



Kit
HM 700



1/4" F. Spray angle 20°. Max. 700 bar / 100 °C. Delivery time of approx. 1 week

R+M Nr.	D
655 700 520	02
655 700 525	025
655 700 530	03
655 700 535	035
655 700 540	04
655 700 545	045
655 700 550	05
655 700 555	055
655 700 560	06
655 700 570	07

HM 1000



Kit
HM 1000



1/4" F. Spray angle 20°. Max. 1000 bar / 100 °C. Delivery time of approx. 1 week

R+M Nr.	D
655 100 520	02
655 100 525	025
655 100 530	03
655 100 535	035
655 100 540	04
655 100 545	045
655 100 550	05
655 100 555	055
655 100 560	06
655 100 570	07

R+M Nr.
655 100 120
655 100 125
655 100 130
655 100 135
655 100 140
655 100 145
655 100 150
655 100 155
655 100 160
655 100 170

Symbols inlet outlet length material nozzle colour coding