


PURClean365+® Power and 150 - food hose

PURClean365+® Power DN 8

- » PURClean365+® Power - Food hose according to (EC) 1935/2004, (EC) 10/2011 and (EC) 2023/2006.
- » 3-layer plastic hose with a smooth cover.
- » Particularly pressure-stable and flexible up to a maximum of **200 bar** working pressure.
- » Area of application: high-pressure cleaning hose in the food industry.
- » Suitable for water and water mixes of usual cleaning detergents.
- » Suitable for contact with liquid food products
- » Increased 1-layer rot-proof textile mesh.


-40 °C - +60 °C. Fittings stainless steel

Female thread DKR 3/8"




R+M Nr.	
478 054 610 9	10.0 m
478 054 615 9	15.0 m
478 054 620 9	20.0 m
478 054 625 9	25.0 m

Male thread AGR 3/8"



R+M Nr.	
478 044 610 9	10.0 m
478 044 615 9	15.0 m
478 044 620 9	20.0 m
478 044 625 9	25.0 m

M22 Quick screw couplings



R+M Nr.	
478 000 610 9	10.0 m
478 000 615 9	15.0 m
478 000 620 9	20.0 m
478 000 625 9	25.0 m



PURClean365+® Power per metre


R+M Nr.	DN			P	BP	Ø	g
303 672 00	8	100 m	3.8 mm	200 bar	>800 bar	15.3 mm	0.15 kg

PURClean365+® 150, DN 11

- » PURClean365+® 150 - Food hose according to (EC) 1935/2004, (EC) 10/2011 and (EC) 2023/2006.
- » 3-layer plastic hose with a smooth cover.
- » Particularly pressure-stable and flexible up to a maximum of **150 bar** working pressure.
- » Area of application: high-pressure cleaning hose in the food industry, also suitable for foam and spray cleaning.
- » Suitable for water and water mixes of usual cleaning detergents.
- » Suitable for contact with liquid food products
- » Increased 1-layer rot-proof textile mesh.


-40 °C - +60 °C. Fittings stainless steel

Female thread DKR 1/2"




R+M Nr.	
479 056 602 59	2.5 m
479 056 610 9	10.0 m
479 056 615 9	15.0 m
479 056 620 9	20.0 m
479 056 625 9	25.0 m
479 056 630 9	30.0 m
479 056 635 9	35.0 m
479 056 640 9	40.0 m

DKR 1/2" : AGR 1/2"




R+M Nr.	
479 057 602 59	2.5 m
479 057 610 9	10.0 m
479 057 615 9	15.0 m
479 057 620 9	20.0 m
479 057 625 9	25.0 m
479 057 630 9	30.0 m
479 057 635 9	35.0 m
479 057 640 9	40.0 m

Male thread (AGR) 1/2"



R+M Nr.	
479 046 602 59	2.5 m
479 046 610 9	10.0 m
479 046 615 9	15.0 m
479 046 620 9	20.0 m
479 046 625 9	25.0 m
479 046 630 9	30.0 m
479 046 635 9	35.0 m
479 046 640 9	40.0 m

Female thread DKR 3/8"




R+M Nr.	
479 054 602 59	2.5 m
479 054 610 9	10.0 m
479 054 615 9	15.0 m
479 054 620 9	20.0 m
479 054 625 9	25.0 m
479 054 630 9	30.0 m
479 054 635 9	35.0 m
479 054 640 9	40.0 m

DKR 3/8" : AGR 3/8"



R+M Nr.	
479 055 602 59	2.5 m
479 055 610 9	10.0 m
479 055 615 9	15.0 m
479 055 620 9	20.0 m
479 055 625 9	25.0 m
479 055 630 9	30.0 m
479 055 635 9	35.0 m
479 055 640 9	40.0 m

Male thread (AGR) 3/8"



R+M Nr.	
479 044 602 59	2.5 m
479 044 610 9	10.0 m
479 044 615 9	15.0 m
479 044 620 9	20.0 m
479 044 625 9	25.0 m
479 044 630 9	30.0 m
479 044 635 9	35.0 m
479 044 640 9	40.0 m

PURClean365+® 150 per metre

R+M Nr.	DN			P	BP	Ø	g
303 681 50	11	100 m	5.0 mm	150 bar	>550 bar	20.5 mm	0.27 kg

