

**PURClean365+® - food hose**

**PURClean365+® 100**

Female thread DKR 1/2"



Male thread (AGR) 1/2"



-20 °C - +100 °C. Fittings stainless steel

**PURClean365+® 100 per metre**

R+M Nr.	DN	↔	⊗	P 20 °C	P 100 °C	BP 20 °C	⊞
303 661 00	12	10 - 100 m	4.5	40 bar	18 bar	≥ 200 bar	0.25 kg

R+M Nr.	↔
477 056 602 59	2.5 m
477 056 610 9	10.0 m
477 056 615 9	15.0 m
477 056 620 9	20.0 m
477 056 625 9	25.0 m
477 056 630 9	30.0 m
477 056 635 9	35.0 m
477 056 640 9	40.0 m

R+M Nr.	↔
477 046 602 59	2.5 m
477 046 610 9	10.0 m
477 046 615 9	15.0 m
477 046 620 9	20.0 m
477 046 625 9	25.0 m
477 046 630 9	30.0 m
477 046 635 9	35.0 m
477 046 640 9	40.0 m

**PURClean365+® - food hose**

**Screw fittings for PURClean365+®**



1/2" M with 60° cone. Stainless steel. Max. 50 bar

R+M Nr.	DN
329 412 129	12



1/2" F with 60° cone. Stainless steel. Max. 50 bar

R+M Nr.	DN
329 512 129	12



1/2" F. Stainless steel. Max. 50 bar. Flat sealing

R+M Nr.	DN
329 612 129	12

**PURClean365+® - 40 food hoses with the professional flat ST-3225**

**Food Special SET**

Professional **ST-3225** gun with progressive closing system and coupling **ST-3100**. Inlet 1/2" F swivel. Stainless steel. Max. 24.5 bar or 60 bar. Max. 120 l/min / 100 °C. with **PURClean365+ 40** food hose 1/2" male thread AGR. 45 bar working pressure at 70 °C

**ST-3225 / PURClean365+ 40 blue**

**ST-3225 / PURClean365+ 40 yellow**

**ST-3225 / PURClean365+ 40 green**

**ST-3225 / PURClean365+ 40 red**



LTF



LTF



LTF



LTF



R+M Nr.	ST-3225 P	↔
476 046 620 91	24.5 bar	20 m
476 046 625 91	24.5 bar	25 m
476 046 630 91	24.5 bar	30 m
476 046 620 92	60 bar	20 m
476 046 625 92	60 bar	25 m
476 046 630 92	60 bar	30 m

R+M Nr.	ST-3225 P	↔
476 346 420 91	24.5 bar	20 m
476 346 425 91	24.5 bar	25 m
476 346 430 91	24.5 bar	30 m
476 346 420 92	60 bar	20 m
476 346 425 92	60 bar	25 m
476 346 430 92	60 bar	30 m

R+M Nr.	ST-3225 P	↔
476 446 220 91	24.5 bar	20 m
476 446 225 91	24.5 bar	25 m
476 446 230 91	24.5 bar	30 m
476 446 220 92	60 bar	20 m
476 446 225 92	60 bar	25 m
476 446 230 92	60 bar	30 m

R+M Nr.	ST-3225 P	↔
476 246 720 91	24.5 bar	20 m
476 246 725 91	24.5 bar	25 m
476 246 730 91	24.5 bar	30 m
476 246 720 92	60 bar	20 m
476 246 725 92	60 bar	25 m
476 246 730 92	60 bar	30 m

**Symbols** ⊗ marking ⊕ inlet ⊖ outlet DN nominal diameter P pressure ↔ length ⊞ weight TYP type °C temperature ⊗ wall thickness mm