

Höchstdruckverschraubungen 500 bar

Handverschraubungen




HV M22 : IG. Edelstahl

R+M Nr.	⊙
561 39	M22 : 1/4"
561 59	M22 : 3/8"



HV M22 : AG. Edelstahl

R+M Nr.	⊙
561 49	M22 : 1/4"
561 69	M22 : 3/8"



Stützring

R+M Nr.	VPE
050 001 440	1
781 021 391 21	100



O-Ring

R+M Nr.	VPE
790 24	1
790 241 00	100

Gegennippel



M22 AG : AG. Edelstahl

R+M Nr.	⊙
565 39	M22 : 1/4"
565 59	M22 : 3/8"
565 69	M22 : 1/2"



M22 AG : IG. Edelstahl

R+M Nr.	⊙
565 29	M22 : 1/4"
565 49	M22 : 3/8"

Doppelnippel mit 60° Konus



AG : AG. Edelstahl

R+M Nr.	⊙
570 79	3/8" : 3/8"
570 89	3/8" : 1/2"
596 143 81	M22 : 3/8"
596 141 21	M22 : 1/2"



AG : AG. Stahl verzinkt

R+M Nr.	⊙
570 78	3/8" : 3/8"
570 88	3/8" : 1/2"
581 141 21	M22 : 1/2"

Schlauchverbinder



DKOS M22 AG : AG. Edelstahl

R+M Nr.	⊙
593 142	M22 : M22



M22 AG : AG. Edelstahl

R+M Nr.	⊙
569 59	M22 : M22



M22 AG. Schwere Ausführung mit Gummischutzkappe. Edelstahl. Max. 500 bar

R+M Nr.
569 49



Gummi

R+M Nr.
569 60

Schutzkappen

Symbole ⊙ Gewinde VPE Verpackungseinheit DN Nennweite ↑ Höhe