

Suttner quick screw couplings ST-740 and nipples ST-741

Quick screw couplings ST-740 and nipples ST-741



M24 F : M.
Max. 700 bar / 150 °C



M24 F : M.
Max. 700 bar / 150 °C



M : M24 M.
Max. 700 bar / 150 °C



M24 M : M24 M.
Max. 700 bar / 150 °C

⊙
3/8"
1/2"
M24

R+M Nr.
200 740 501
200 740 503

R+M Nr.
200 740 601

R+M Nr.
200 741 501
200 741 503

R+M Nr.
200 741 600



M24 F : F.
Max. 700 bar / 150 °C



M24 F : F.
Max. 700 bar / 150 °C



F : M24 M.
Max. 700 bar / 150 °C

⊙
1/4"
3/8"

R+M Nr.
200 740 504
200 740 502

R+M Nr.
200 740 604
200 740 602

R+M Nr.
200 741 504
200 741 502

Seals



O-ring - ST-740

R+M Nr.
050 000 408



O-ring - ST-741

R+M Nr.
050 001 000



Back ring - ST-740

R+M Nr.
050 000 407

Suttner ultra high pressure quick couplings ST-45-600

Couplings and plug ST-45-600



Coupling : M. Stainless steel.
Max. 600 bar / 150 °C



Coupling : M. Stainless steel.
Max. 600 bar / 150 °C



Plug : F. Stainless steel.
Max. 600 bar / 150 °C

⊙	DN
1/4"	8

R+M Nr.	i
200 045 600	57 mm

R+M Nr.	i
200 045 605	57 mm

R+M Nr.	i
040 005 468	40 mm



O-ring. 11x1.5

R+M Nr.
050 000 020



Back ring. 11x14x1

R+M Nr.
050 001 430



O-ring. 10x2.5

R+M Nr.
050 000 160