

Ultra high pressure hoses

Hoses with double wire braid and wrapped cover. Type 2SC. Nominal diameter 10. Safety factor 3.5. Fittings stainless steel. Max. 150 °C

Female thread (DKOS)		Male thread (AGR)		Quick screw couplings																																																													
M22 : M22	M22 : M22	3/8" : 3/8"	3/8" : 3/8"	M22 : M22	M22 : M22																																																												
maxpressure. Type 2SC. Max. 500 bar	Type 2SC. Max. 500 bar	maxpressure. Type 2SC. Max. 500 bar	Type 2SC. Max. 500 bar	maxpressure. Type 2SC. Max. 500 bar	Type 2SC. Max. 500 bar																																																												
<table border="1"><thead><tr><th>R+M Nr.</th><th>↔</th></tr></thead><tbody><tr><td>358 177 310 9</td><td>10 m</td></tr><tr><td>358 177 315 9</td><td>15 m</td></tr><tr><td>358 177 320 9</td><td>20 m</td></tr><tr><td>358 177 330 9</td><td>30 m</td></tr></tbody></table>	R+M Nr.	↔	358 177 310 9	10 m	358 177 315 9	15 m	358 177 320 9	20 m	358 177 330 9	30 m	<table border="1"><thead><tr><th>R+M Nr.</th><th>↔</th></tr></thead><tbody><tr><td>364 177 310 9</td><td>10 m</td></tr><tr><td>364 177 315 9</td><td>15 m</td></tr><tr><td>364 177 320 9</td><td>20 m</td></tr><tr><td>364 177 330 9</td><td>30 m</td></tr></tbody></table>	R+M Nr.	↔	364 177 310 9	10 m	364 177 315 9	15 m	364 177 320 9	20 m	364 177 330 9	30 m	<table border="1"><thead><tr><th>R+M Nr.</th><th>↔</th></tr></thead><tbody><tr><td>358 144 310 9</td><td>10 m</td></tr><tr><td>358 144 315 9</td><td>15 m</td></tr><tr><td>358 144 320 9</td><td>20 m</td></tr><tr><td>358 144 330 9</td><td>30 m</td></tr></tbody></table>	R+M Nr.	↔	358 144 310 9	10 m	358 144 315 9	15 m	358 144 320 9	20 m	358 144 330 9	30 m	<table border="1"><thead><tr><th>R+M Nr.</th><th>↔</th></tr></thead><tbody><tr><td>364 144 310 9</td><td>10 m</td></tr><tr><td>364 144 315 9</td><td>15 m</td></tr><tr><td>364 144 320 9</td><td>20 m</td></tr><tr><td>364 144 330 9</td><td>30 m</td></tr></tbody></table>	R+M Nr.	↔	364 144 310 9	10 m	364 144 315 9	15 m	364 144 320 9	20 m	364 144 330 9	30 m	<table border="1"><thead><tr><th>R+M Nr.</th><th>↔</th></tr></thead><tbody><tr><td>358 100 310 9</td><td>10 m</td></tr><tr><td>358 100 315 9</td><td>15 m</td></tr><tr><td>358 100 320 9</td><td>20 m</td></tr><tr><td>358 100 330 9</td><td>30 m</td></tr></tbody></table>	R+M Nr.	↔	358 100 310 9	10 m	358 100 315 9	15 m	358 100 320 9	20 m	358 100 330 9	30 m	<table border="1"><thead><tr><th>R+M Nr.</th><th>↔</th></tr></thead><tbody><tr><td>364 100 310 9</td><td>10 m</td></tr><tr><td>364 100 315 9</td><td>15 m</td></tr><tr><td>364 100 320 9</td><td>20 m</td></tr><tr><td>364 100 330 9</td><td>30 m</td></tr></tbody></table>	R+M Nr.	↔	364 100 310 9	10 m	364 100 315 9	15 m	364 100 320 9	20 m	364 100 330 9	30 m
R+M Nr.	↔																																																																
358 177 310 9	10 m																																																																
358 177 315 9	15 m																																																																
358 177 320 9	20 m																																																																
358 177 330 9	30 m																																																																
R+M Nr.	↔																																																																
364 177 310 9	10 m																																																																
364 177 315 9	15 m																																																																
364 177 320 9	20 m																																																																
364 177 330 9	30 m																																																																
R+M Nr.	↔																																																																
358 144 310 9	10 m																																																																
358 144 315 9	15 m																																																																
358 144 320 9	20 m																																																																
358 144 330 9	30 m																																																																
R+M Nr.	↔																																																																
364 144 310 9	10 m																																																																
364 144 315 9	15 m																																																																
364 144 320 9	20 m																																																																
364 144 330 9	30 m																																																																
R+M Nr.	↔																																																																
358 100 310 9	10 m																																																																
358 100 315 9	15 m																																																																
358 100 320 9	20 m																																																																
358 100 330 9	30 m																																																																
R+M Nr.	↔																																																																
364 100 310 9	10 m																																																																
364 100 315 9	15 m																																																																
364 100 320 9	20 m																																																																
364 100 330 9	30 m																																																																

Hoses with double wire braid and wrapped cover. Nominal diameter 10. Fittings stainless steel. Max. 150 °C

Quick screw couplings																																
M24 : M24	M24 : M24	M24 : M24																														
maxpressure. Type 2SC. Max. 500 bar	Type 2SC. Max. 500 bar	Type 2SN. Max. 600 bar																														
<table border="1"><thead><tr><th>R+M Nr.</th><th>↔</th></tr></thead><tbody><tr><td>358 197 310 9</td><td>10 m</td></tr><tr><td>358 197 315 9</td><td>15 m</td></tr><tr><td>358 197 320 9</td><td>20 m</td></tr><tr><td>358 197 330 9</td><td>30 m</td></tr></tbody></table>	R+M Nr.	↔	358 197 310 9	10 m	358 197 315 9	15 m	358 197 320 9	20 m	358 197 330 9	30 m	<table border="1"><thead><tr><th>R+M Nr.</th><th>↔</th></tr></thead><tbody><tr><td>364 197 310 9</td><td>10 m</td></tr><tr><td>364 197 315 9</td><td>15 m</td></tr><tr><td>364 197 320 9</td><td>20 m</td></tr><tr><td>364 197 330 9</td><td>30 m</td></tr></tbody></table>	R+M Nr.	↔	364 197 310 9	10 m	364 197 315 9	15 m	364 197 320 9	20 m	364 197 330 9	30 m	<table border="1"><thead><tr><th>R+M Nr.</th><th>↔</th></tr></thead><tbody><tr><td>368 697 610 9</td><td>10 m</td></tr><tr><td>368 697 615 9</td><td>15 m</td></tr><tr><td>368 697 620 9</td><td>20 m</td></tr><tr><td>368 697 630 9</td><td>30 m</td></tr></tbody></table>	R+M Nr.	↔	368 697 610 9	10 m	368 697 615 9	15 m	368 697 620 9	20 m	368 697 630 9	30 m
R+M Nr.	↔																															
358 197 310 9	10 m																															
358 197 315 9	15 m																															
358 197 320 9	20 m																															
358 197 330 9	30 m																															
R+M Nr.	↔																															
364 197 310 9	10 m																															
364 197 315 9	15 m																															
364 197 320 9	20 m																															
364 197 330 9	30 m																															
R+M Nr.	↔																															
368 697 610 9	10 m																															
368 697 615 9	15 m																															
368 697 620 9	20 m																															
368 697 630 9	30 m																															

Hoses with double wire braid and smooth cover. Nominal diameter 6. Fittings stainless steel. Max. 150 °C

Quick screw couplings / male thread (AGR)																																
M22 : M22	M22 : 1/8"	1/4" : 1/4"																														
maxpressure. Type flexy 500. Max. 500 bar	Type flexy 500. Max. 500 bar	Type flexy 500. Max. 500 bar																														
<table border="1"><thead><tr><th>R+M Nr.</th><th>↔</th></tr></thead><tbody><tr><td>338 000 310 9</td><td>10 m</td></tr><tr><td>338 000 315 9</td><td>15 m</td></tr><tr><td>338 000 320 9</td><td>20 m</td></tr><tr><td>338 000 330 9</td><td>30 m</td></tr></tbody></table>	R+M Nr.	↔	338 000 310 9	10 m	338 000 315 9	15 m	338 000 320 9	20 m	338 000 330 9	30 m	<table border="1"><thead><tr><th>R+M Nr.</th><th>↔</th></tr></thead><tbody><tr><td>424 300 010 9</td><td>10 m</td></tr><tr><td>424 300 015 9</td><td>15 m</td></tr><tr><td>424 300 020 9</td><td>20 m</td></tr><tr><td>424 300 030 9</td><td>30 m</td></tr></tbody></table>	R+M Nr.	↔	424 300 010 9	10 m	424 300 015 9	15 m	424 300 020 9	20 m	424 300 030 9	30 m	<table border="1"><thead><tr><th>R+M Nr.</th><th>↔</th></tr></thead><tbody><tr><td>424 344 010 9</td><td>10 m</td></tr><tr><td>424 344 015 9</td><td>15 m</td></tr><tr><td>424 344 020 9</td><td>20 m</td></tr><tr><td>424 344 030 9</td><td>30 m</td></tr></tbody></table>	R+M Nr.	↔	424 344 010 9	10 m	424 344 015 9	15 m	424 344 020 9	20 m	424 344 030 9	30 m
R+M Nr.	↔																															
338 000 310 9	10 m																															
338 000 315 9	15 m																															
338 000 320 9	20 m																															
338 000 330 9	30 m																															
R+M Nr.	↔																															
424 300 010 9	10 m																															
424 300 015 9	15 m																															
424 300 020 9	20 m																															
424 300 030 9	30 m																															
R+M Nr.	↔																															
424 344 010 9	10 m																															
424 344 015 9	15 m																															
424 344 020 9	20 m																															
424 344 030 9	30 m																															

Symbols ↔ length | height ⊕ inlet ⊖ outlet DN nominal diameter P pressure ⊗ weight ⊙ thread ⊘ diameter D thread TYP type → flow