
ST-230 Pressure regulating valve-set



ST-230 with connection, ball valve, stainless steel lance 400 mm and hose 1,000 mm. Max. 250 bar / 30 l/min / 95 °C

R+M Nr.	œ	Ð
530 404 1	M22 M	M22 F

Suttner chemical suction set



Suction set with suction hose 1,500 mm, suction filters ST-31 and chemical-resistant plastic tube 320 mm. The tube keeps the suction filter at the deepest point.


R+M Nr.	TYP	DN
200 031 500	clear PVC hose	6 mm
200 031 510	reinforced PVC hose blue	9 mm
200 031 520	reinforced PVC hose yellow	9 mm
200 031 530	reinforced PVC hose clear	9 mm



Suction set with filter check valve ST-32 and stain- Clamps with hexagon screw. 1 9 mm less steel tube 350 mm.

R+M Nr.	DN	
200 032 601	6 mm	
200 032 602	8 mm	
200 032 603	10 mm	

Suttner foam injectors



Max. 250 bar / 60 °C. Mixing of chemicals approx. 0 - 11.5 %

R+M Nr.		TYP	D	Œ.	Ð
200 060 700	1	ST-60.1	1.6	3/8" M	3/8" F
200 060 710	1	ST-60.1	1.8	3/8" M	3/8" F
050 000 370	2	o-ring			
200 061 500	3	metering	valve	hose tai	I Ø 6 mm

Repair kits



Chemical check valve. Hose tail 6 mm

R+M Nr.
200 060 725

Hose clamps

1.4016 stainless steel housing and band. Hexagon screw zinc-plated. Worm gear high

Flat tape inner sides with turned up rims. According to DIN 3017, W2



R+M Nr.	VPE	DN	
735 10	1	6 mm	
735 20	1	8 mm	
735 30	1	9/10 mm	

R+M Nr.	VPE	DN	
735 101 00	100	6 mm	
735 201 00	100	8 mm	
735 301 00	100	9/10 mm	

W4 and W5 completely rust-free, is available on request