

## Accessories injectors

## Return valves



Hose tail : M14 M. V2A.  
With o-ring

**R+M Nr.**

200 163 350



1/4" M : M14 M. V2A.  
With o-ring

**R+M Nr.**

200 163 356



1/4" M : M18 M. (ST-164).  
With o-ring

**R+M Nr.**

200 164 366

0

0

O-rings

**R+M Nr.**

050 000 264

2.9 x 1.78

050 000 300

10.82 x 1.78



Hose tail 9 mm : M14 M.  
V4A Extreme.  
Highest chemical resistance.  
With o-ring

**R+M Nr.**

200 163 351



1/4" M : M14 M. V4A Extreme.  
Highest chemical resistance.  
With o-ring

**R+M Nr.**

200 163 352

0

0

O-rings.  
Highest chemical resistance

**R+M Nr.**

050 001 450

2.9 x 1.78

050 000 302

10.82 x 1.78

## Plug



M14 M. Compressed air connection  
(ST-160.2/ST-160.3/ST-162/ST-167/  
ST-168).

Without o-ring

**R+M Nr.**

040 003 625



M18 M. Compressed air connection  
(ST-164).

With o-ring

**R+M Nr.**

200 164 345

## Ultra High Pressure Filter



40 mm



Stainless steel with brass mesh holder and stainless steel strainer. Suitable  
as inlet water filter for ST-164.

Max. 400 bar / 100 °C

**R+M Nr.**

200 163 100

M 22 M

3/8" M

## Two component inlet



M14 M. : M14 F : M14 F. V2A. (ST-160/ST-160.2/ST-160.3/ST-162/ST-164/  
ST-166/ST-167/ST-168). With o-rings

**R+M Nr.**

200 164 355



00 00

Rep. Kit. 2 x 2 O-rings

**R+M Nr.**

200 164 365