

## Accessories for hose reels

## Wall swivel brackets ST 14 / ST 20



180° swivel

R+M Nr.	★	Ⓜ
741 00	●	zinc-plated steel
741 01	●	stain. steel V2A / AISI 304

## Wall swivel brackets ST 30 / ST 40



180° swivel

R+M Nr.	★	Ⓜ
741 001	■	zinc-plated steel
741 011	■	stain. steel V2A / AISI 304

## Wall swivel brackets ST 40



180° swivel

R+M Nr.	★	Ⓜ
741 003	▲	zinc-plated steel
741 012	▲	stain. steel V2A / AISI 304

## Counterplates ST 40



R+M Nr.	★	Ⓜ
741 002	▲▲	stain. steel V2A / AISI 304

## Swivels ST-322

3/8" F : 3/8" M. DN 10.  
Max. 400 bar / 90 °C

R+M Nr.	ⓘ
200 322 500	65 mm

1/2" F : 3/8" M. DN 10.  
Max. 300 bar / 90 °C

R+M Nr.	ⓘ
200 322 510	65 mm

1/2" F : 1/2" M. DN 12.  
Max. 300 bar / 90 °C

R+M Nr.	ⓘ
200 322 520	67 mm

1/2" F : 1/2" M. DN 12.  
Max. 300 bar / 90 °C

R+M Nr.	ⓘ
200 322 522	68 mm

## ST / SoST



Swivel 200 bar

R+M Nr.	Ⓞ
750 400 1	3/4"



Seal kit swivel 200 bar

R+M Nr.	Ⓜ
750 400 2	3/4"

## Repair kit ST-322



Repair kit swivels ST-322

R+M Nr.
200 322 490

## Hose guides



Wall hose guide frame. 50 x 37 mm

R+M Nr.
741 06

1/4" F : 3/8" M. Housing and axle  
stainless steel. Max. 600 bar / 90 °C


R+M Nr.	ⓘ
750 280 0	59 mm



Seal kit swivel 750 280 0

R+M Nr.
750 200 2

## Hose stops

Hose stop with six exchangeable  
inserts

R+M Nr.
741 03

## Bolt sets

Stainless steel. Set for bracket  
inserts

R+M Nr.
741 02

Symbols ★ marking Ⓞ colour Ⓞ inlet Ⓞ outlet DN nominal diameter P pressure ↔ length Ⓞ weight TYP type °C temperature