

## Ultra high pressure swivels

### Elbow swivel



1/2" M : 1/2" F. Inox.  
Max. 600 bar

R+M Nr.
178 261 330 00

### ST-350 swivel



3/8" M : 3/8" F.  
Max. 600 bar

R+M Nr.
200 350 010



Repair kit ST-350

R+M Nr.
200 300 120

### R+M swivel



1/4" F : 3/8" M. Housing  
and axle stainless steel.  
Max. 600 bar / 90 °C

R+M Nr.
750 280 0



Seal kit swivel 750 280 0


R+M Nr.
750 200 2

### ST-351 swivel



1/2" M : 1/2" F.  
Max. 600 bar

R+M Nr.
200 351 510



Repair kit swivel ST-351

R+M Nr.
200 351 400

## Reduction nipple



Stainless steel. 500 bar

R+M Nr.	⊖	⊕
040 002 207	1/4" F	1/8" M

## ST-550 foot valves



Housing stainless steel.  
Valve stainless steel.  
Rubber feet.  
Max. 500 bar / 80 l/min / 150 °C

R+M Nr.	⊖	⊕
200 550 600	1/4" F	1/4" F



Housing stainless steel.  
Valve stainless steel.  
Rubber feet.  
Max. 500 bar / 80 l/min / 150 °C

R+M Nr.	⊖	⊕
200 550 620	M22 F	M22 M

## ST-540 foot valves



Incl. HP-gun ST-2750.  
Material housing powdercoated  
steel.  
Rubber feet.  
Max. 500 bar / 30 l/min / 150 °C

R+M Nr.	⊖	⊕
200 540 550	1/4" M	3/8" F



Incl. HP-gun ST-2750.  
Material housing powdercoated  
steel.  
Rubber feet.  
Max. 500 bar / 30 l/min / 150 °C

R+M Nr.	⊖	⊕
200 540 560	M22 M	M22 M

Symbols ⊖ length ⊕ inlet ⊖ outlet ⊗ diameter ⊐ pressure