

Contrôleurs de débit THP, Suttner

Contrôleurs de débit ST-505, 600 bar



Flotteur ST-505 inox
avec perçage

R+M Nr.
200 005 301

R+M Nr.	câble ⇄
200 005 435	1.200 mm
200 005 438	3.500 mm

Flotteur inox avec perçage.
Contact 1 A - 250 V.

R+M Nr.	⊙	Montage	fermeture/ouverture	°C	⇄	Câble ⇄
200 505 706	3/8" F	vertical	3,3/1,8	80	30 l/min	1.200 mm
200 505 709	3/8" F	vertical	2,9/1,7	80	30 l/min	3.500 mm



Flotteur ST-505 sans
perçage

R+M Nr.	câble ⇄
200 005 435	1.200 mm
200 005 438	3.500 mm

Flotteur laiton sans perçage.
Contact 1 A - 250 V.

R+M Nr.	⊙	Montage	fermeture/ouverture	°C	⇄	Câble ⇄
200 505 708	3/8" F	vertical	3,3/1,8	80	30 l/min	1.200 mm
200 505 711	3/8" F	vertical	3,3/1,8	80	30 l/min	3.500 mm



Flotteur ST-505 inox
sans perçage

R+M Nr.
200 005 311

Contact REED

R+M Nr.
200 005 438

Flotteur inox sans perçage. Contact 1 A - 250 V.

R+M Nr.	⊙	Montage	fermeture/ouverture	°C	⇄	Câble ⇄
205 505 707	3/8" F	vertical	1,8/1,3	80	30 l/min	1.200 mm