

CARWASH COMFORT - the new hose wonder in self-service washing bays

1/4" : 1/4"



Female thread (DKR)

R+M Nr.	↔	length
463 052 303 5		3.5 m
463 052 303 7		3.7 m
463 052 304		4.0 m
463 052 304 2		4.2 m
463 052 304 5		4.5 m
463 052 304 7		4.7 m
463 052 305		5.0 m
463 052 305 5		5.5 m
463 052 306		6.0 m

3/8" : 3/8"



Female thread (DKR)

R+M Nr.	↔	length
463 054 303 5		3.5 m
463 054 303 7		3.7 m
463 054 304		4.0 m
463 054 304 2		4.2 m
463 054 304 5		4.5 m
463 054 304 7		4.7 m
463 054 305		5.0 m
463 054 305 5		5.5 m
463 054 306		6.0 m

M14 : M14



Female thread (DKOL)

R+M Nr.	↔	length
463 072 303 5		3.5 m
463 072 303 7		3.7 m
463 072 304		4.0 m
463 072 304 2		4.2 m
463 072 304 5		4.5 m
463 072 304 7		4.7 m
463 072 305		5.0 m
463 072 305 5		5.5 m
463 072 306		6.0 m

M18 : M18



Female thread (DKOL)

R+M Nr.	↔	length
463 076 303 5		3.5 m
463 076 303 7		3.7 m
463 076 304		4.0 m
463 076 304 2		4.2 m
463 076 304 5		4.5 m
463 076 304 7		4.7 m
463 076 305		5.0 m
463 076 305 5		5.5 m
463 076 306		6.0 m

3/8" : 3/8"



Male thread (AGR)

R+M Nr.	↔	length
463 044 303 5		3.5 m
463 044 303 7		3.7 m
463 044 304		4.0 m
463 044 304 2		4.2 m
463 044 304 5		4.5 m
463 044 304 7		4.7 m
463 044 305		5.0 m
463 044 305 5		5.5 m
463 044 306		6.0 m



Female thread (DKR)

R+M Nr.	↔	length
464 052 303 5		3.5 m
464 052 303 7		3.7 m
464 052 304		4.0 m
464 052 304 2		4.2 m
464 052 304 5		4.5 m
464 052 304 7		4.7 m
464 052 305		5.0 m
464 052 305 5		5.5 m
464 052 306		6.0 m



Female thread (DKR)

R+M Nr.	↔	length
464 054 303 5		3.5 m
464 054 303 7		3.7 m
464 054 304		4.0 m
464 054 304 2		4.2 m
464 054 304 5		4.5 m
464 054 304 7		4.7 m
464 054 305		5.0 m
464 054 305 5		5.5 m
464 054 306		6.0 m



Female thread (DKOL)

R+M Nr.	↔	length
464 072 303 5		3.5 m
464 072 303 7		3.7 m
464 072 304		4.0 m
464 072 304 2		4.2 m
464 072 304 5		4.5 m
464 072 304 7		4.7 m
464 072 305		5.0 m
464 072 305 5		5.5 m
464 072 306		6.0 m



Female thread (DKOL)

R+M Nr.	↔	length
464 076 303 5		3.5 m
464 076 303 7		3.7 m
464 076 304		4.0 m
464 076 304 2		4.2 m
464 076 304 5		4.5 m
464 076 304 7		4.7 m
464 076 305		5.0 m
464 076 305 5		5.5 m
464 076 306		6.0 m



Male thread (AGR)

R+M Nr.	↔	length
464 044 303 5		3.5 m
464 044 303 7		3.7 m
464 044 304		4.0 m
464 044 304 2		4.2 m
464 044 304 5		4.5 m
464 044 304 7		4.7 m
464 044 305		5.0 m
464 044 305 5		5.5 m
464 044 306		6.0 m



Female thread (DKR)

R+M Nr.	↔	length
465 052 303 5		3.5 m
465 052 303 7		3.7 m
465 052 304		4.0 m
465 052 304 2		4.2 m
465 052 304 5		4.5 m
465 052 304 7		4.7 m
465 052 305		5.0 m
465 052 305 5		5.5 m
465 052 306		6.0 m



Female thread (DKR)

R+M Nr.	↔	length
465 054 303 5		3.5 m
465 054 303 7		3.7 m
465 054 304		4.0 m
465 054 304 2		4.2 m
465 054 304 5		4.5 m
465 054 304 7		4.7 m
465 054 305		5.0 m
465 054 305 5		5.5 m
465 054 306		6.0 m



Female thread (DKOL)

R+M Nr.	↔	length
465 072 303 5		3.5 m
465 072 303 7		3.7 m
465 072 304		4.0 m
465 072 304 2		4.2 m
465 072 304 5		4.5 m
465 072 304 7		4.7 m
465 072 305		5.0 m
465 072 305 5		5.5 m
465 072 306		6.0 m



Female thread (DKOL)

R+M Nr.	↔	length
465 076 303 5		3.5 m
465 076 303 7		3.7 m
465 076 304		4.0 m
465 076 304 2		4.2 m
465 076 304 5		4.5 m
465 076 304 7		4.7 m
465 076 305		5.0 m
465 076 305 5		5.5 m
465 076 306		6.0 m



Male thread (AGR)

R+M Nr.	↔	length
465 044 303 5		3.5 m
465 044 303 7		3.7 m
465 044 304		4.0 m
465 044 304 2		4.2 m
465 044 304 5		4.5 m
465 044 304 7		4.7 m
465 044 305		5.0 m
465 044 305 5		5.5 m
465 044 306		6.0 m

Symbols ↔ length