What is the difference between the versions freeze stop and weep?



pressure spray devices. The physical effect that liquids in motion tend to freeze to a lesser extent forms the basis of both versions. Therefore, both the weep as well as the freeze stop version let water pass through the valve (in case of different pressures and under the circumstances) even if the spray gun is closed in order to keep the water which is in piping, hose and spray device in motion.

The picture illustrates the different effects regarding diverse winter safety methods of high

The weep high pressure spray guns let a reduced water quantity pass through even if the trigger of the gun is not pulled as there is a notch in the seal seat of the valve. This is ensured in high pressure when the high pressure pump is in operation as well as in low pressure in case of water pipe pressure.

The so called freeze stop spray guns are equipped with a valve in valve technology. The operating valve which is driven by the spray gun trigger includes the real automatically operating freeze stop piston. For cleaning applications the spray gun is opened and closed as usual by the operating valve. The integrated freeze stop valve only comes into operation when there is low pressure (water pipe pressure). It is opened in a spring driven way if the pressure is lower than 5 bar. If the pressure increases e.g. by switching on the high pressure pump the freeze stop valve closes automatically. This improves the comfort of washing as there is no water coming out of the gun when taking it out of the lance holder.



High pressure spray guns for self-service car wash

ST-2300 freeze stop



Professional gun. Freeze stop version. Max. 310 bar / 45 l/min / 150 °C

R+M Nr.	Ð	e
202 300 582	1/4" F	3/8" F swivel

Weep

R+M Nr.

202 300 491

ST-2300 weep



Professional gun. Weep version. Max. 310 bar / 45 l/min / 150 °C

R+M Nr.	Ð	Œ.
202 300 580	1/4" F	3/8" F

ST-2300 weep



Professional gun. Weep version. Max. 310 bar / 45 l/min / 150 °C

R+M Nr.	⊖	Œ
202 300 581	1/4" F	3/8" F swivel

Seal kits

Valve complete ST-2300







R+M Nr.

202 300 457


Freeze stop

1/4" F: 3/8" F. ST-2300 R+M Nr.

200 301 050

ST-301 swivels





Repair kit ST-301

R+M Nr. 200 300 100

ST-1100 R+M Nr. 201 100 403

202 300 490

Standard

R+M Nr.



Professional gun. Weep version. Max. 210 bar / 25 l/min / 150 °C

R+M Nr.	Θ	Œ
201 100 535	1/4" F	3/8" F

ST-1100 weep



Professional gun. Weep version. Max. 210 bar / 25 l/min / 150 °C

R+M Nr.	⊖	Œ
201 100 530	1/4" F	3/8" F swivel

ST-1100 without trigger



Professional gun without valve. Max. 210 bar / 25 l/min / 150 °C

R+M Nr.	Θ	Œ
201 100 570	1/4" F	3/8" F swivel