

easywash365+ Prewashing trolley

new

- » Stainless steel
- » 2 separate areas
- » Water pipe connection: ST-45 plug nipple for 1/2" DN 13 or 3/4" DN 19
- » Drain tap and nozzle for DN 13
- » Incl. Intake hose with filter and check valve
- » Storage of detergent canisters up to 30 liters
- » The water and detergent supply is automatically closed or opened by a float valve



R+M Nr.		
105 830	ST-45	ball valve

Wheel scrubber WHEELBLASTER PRO

- » Made out of stainless steel
- » 4 nozzles tips are required
- » Variable height and swing adjustment
- » Multiple cleaning heads can be installed
- » High impact at distance
- » DYTIs swivel
- » Rotor arm 160/160 mm
- » **Delivery about 3 weeks**

The Wheelblaster Pro is the new standard for vehicle wash systems. The complete wash head can be placed nearly anywhere you wish and has variable height and swing adjustment. The unit must be equipped with 4 stabilizer nozzles. These four 0° stabilizer nozzles increase distance and impact to achieve optimal cleaning. It is possible to cover a larger cleaning area by mounting various cleaning heads on the 1 meter high stand



action-	
distance	cleaning surface
250 mm	450 mm
500 mm	700 mm
750 mm	950 mm
1,000 mm	1,200 mm

R+M Nr.						
108 845 41	incl. stand	120°	275 bar	up to 2,000 rpm	3/8" F	11.5 kg
108 845 91	excl. stand	120°	275 bar	up to 2,000 rpm	3/8" F	4.2 kg

Wheel scrubber



Buffed stainless steel. Accessories for automatic car wash. Turbo swivel. Rotating arm is powered by water. Adjustable in height. Connectable with a hose of the pumping system.
 4 nozzles 1/8" M NPT are required.
 Rotor 470 / 350 mm.
 Max. 250 bar / 2,000 r.p.m. / 120 °C

R+M Nr.		
108 845 12	standard	3/8" F
108 845 17	high performance	3/8" F

Symbols inlet type pressure revolutions weight material temperature shipment by truck height width