

Handles with water flow



Aluminum handle. Ergonomic handle with insulated grip. Connector suitable for Nito system

R+M Nr.	∅	↔	(M)	°C
527 001 405	34 mm	1020 mm	aluminium	max. 50 °C



Alustiel. Ergonomic handle with insulated grip and ball valve. Connector suitable for Nito system

R+M Nr.	∅	↔	(M)	°C
527 001 406	34 mm	1630 mm	aluminium	max. 50 °C



Aluminum handle. Ergonomic handle with insulated grip. Hose tail suitable for 1/2" and 3/4"

R+M Nr.	∅	↔	(M)	°C
527 001 400	34 mm	1600 mm	aluminium	max. 50 °C



Aluminum handle. Telescopic handle with insulated grip. Hose tail suitable for 1/2" and 3/4"

R+M Nr.	∅	↔	(M)	°C
527 001 402	50 mm	1630 - 2750 mm	aluminium	max. 50 °C

Handles without water flow



Aluminum handle. Ergonomic handle with insulated grip

R+M Nr.	∅	↔	(M)	°C
527 001 403	34 mm	1500 mm	aluminium	max. 50 °C



Aluminum handle. Telescopic handle with insulated grip

R+M Nr.	∅	↔	(M)	°C
527 001 401	50 mm	1630 - 2750 mm	aluminium	max. 50 °C

Symbols (M) material ↔ length ∅ diameter °C temperature