

## easyfarm365+

## Lances



Plug KW. Lance stainless steel, moulded handle 300 mm, valve ST-53 on top, nozzle protector ST-10 with low pressure nozzle and 1/4" M thread for rotating nozzles. Lance without rotating nozzle. Max. 250 bar / 150 °C

R+M Nr.	ISO	⊗	⇄	Ⓒ
200 053 538	300 mm	1/4" M	980 mm	plug KW

## foamblaster ST-76

The **foamblaster ST-76** is designed for applications in agriculture, industry, municipal cleaning and fire fighting technology.

There are injector nozzles with diameters of up to 2.8 mm for high flow rates available for all **easyfoam365+** stainless steel injectors ST-160, ST-164, ST-166 and ST-167.

Material: stainless steel / plastic.

Min. 70 bar for use in combination with an **easyfoam365+** injector unit.

Min. 30 bar for use with water / foamagent premix.

Max. 250 bar / 20 - 60 l/min / 100 °C

R+M Nr.	D	Ⓒ
200 076 615	2,3 mm	1/2" F
200 076 621	2,6 mm	1/2" F
200 076 600	2,7 mm	1/2" F
200 076 624	2,9 mm	1/2" F
200 076 630	3,25 mm	1/2" F
200 076 633	3,4 mm	1/2" F

