

### kommunal365+

#### Lances



Plug ST-3100. Lance stainless steel, moulded handle 400 mm and 1/4" M thread for rotating nozzles. Lance without rotating nozzle. Max. 400 bar / 150 °C

R+M Nr.	ISO	⊖	↔	Ⓢ
200 000 523	400 mm	1/4" M	1000 mm	plug ST-3100



Plug ST-3100. Lance stainless steel, moulded handle 300 mm, valve ST-53 on top, nozzle protector ST-10 with low pressure nozzle and 1/4" M thread for rotating nozzles. Lance without rotating nozzle. Max. 250 bar / 150 °C

R+M Nr.	ISO	⊖	↔	Ⓢ
200 053 537	300 mm	1/4" M	980 mm	plug ST-3100

### foamblaster ST-76

The foamblaster ST-76 is designed for applications in agriculture, industry, municipal cleaning and fire fighting technology.

There are injector nozzles with diameters of up to 2.8 mm for high flow rates available for all **easyfoam365+** stainless steel injectors ST-160, ST-164, ST-166 and ST-167.

Material: stainless steel / plastic.

Min. 70 bar for use in combination with an **easyfoam365+** injector unit.

Min. 30 bar for use with water / foamagent premix.

Max. 250 bar / 20 - 60 l/min / 100 °C

R+M Nr.	D	Ⓢ
200 076 615	2,3 mm	1/2" F
200 076 621	2,6 mm	1/2" F
200 076 600	2,7 mm	1/2" F
200 076 624	2,9 mm	1/2" F
200 076 630	3,25 mm	1/2" F
200 076 633	3,4 mm	1/2" F

