

Suttner rotating nozzles ST-458.1 with ceramic insert

ST-458.1



1/4" F. Spray angle 20°.
120 - 250 bar. Max. 100 °C

| R+M Nr. | D |
|-------------|----|
| 200 458 811 | 11 |
| 200 458 812 | 12 |
| 200 458 815 | 15 |
| 200 458 820 | 20 |
| 200 458 825 | 25 |
| 200 458 830 | 30 |

Kit ST-458.1

| R+M Nr. |
|-------------|
| 200 458 311 |
| 200 458 312 |
| 200 458 315 |
| 200 458 320 |
| 200 458 325 |
| 200 458 330 |

ST-3500 high-flow spray guns



Professional high-flow gun. Stainless steel.
Industrial high pressure cleaning and jetting gun
for municipal cleaning and other industrial cleaning
tasks. Valve piston hardened stainless steel.
Max. 350 bar / 200 l/min / 150 °C

| R+M Nr. | ☺ | ☹ |
|-------------|--------|--------|
| 203 500 500 | 1/2" F | 1/2" F |



Professional high-flow gun. Stainless steel.
Industrial high pressure cleaning and jetting gun
for municipal cleaning and other industrial cleaning
tasks. Valve piston hardened stainless steel. Swivel
stainless steel. Max. 350 bar / 200 l/min / 150 °C

| R+M Nr. | ☺ | ☹ |
|-------------|--------|---------------|
| 203 500 550 | 1/2" F | 1/2" F swivel |

Suttner ultra high pressure lances

Ultra high pressure lances ST-3600 - 600 bar



1/2" M. Lance with grip. Max. 600 bar / 150 °C

| R+M Nr. | ☺ | ☹ | ☺ | M |
|-------------|--------|---------|--------|-----------------|
| 203 600 416 | 1/2" M | 1500 mm | 1/2" M | stainless steel |
| 203 600 415 | 1/2" M | 2000 mm | 1/2" M | stainless steel |

| R+M Nr. |
|---------|
| |
| |



1/2" M. Lance with grip and sleeve 1/4" F NPT stainless steel without high pressure nozzle. Max. 600 bar / 150 °C

| R+M Nr. | ☺ | ☹ | ☺ | M |
|-------------|------------|---------|--------|-----------------|
| 203 600 400 | 1/4" F NPT | 500 mm | 1/2" M | stainless steel |
| 203 600 401 | 1/4" F NPT | 800 mm | 1/2" M | stainless steel |
| 203 600 402 | 1/4" F NPT | 1000 mm | 1/2" M | stainless steel |

| R+M Nr. |
|---------|
| |
| |



1/2" M. Lance with grip for rotating nozzles with 1/4" F (without rotating nozzle). Max. 600 bar / 150 °C

| R+M Nr. | ☺ | ☹ | ☺ | M |
|-------------|--------|---------|--------|-----------------|
| 203 600 411 | 1/4" M | 500 mm | 1/2" M | stainless steel |
| 203 600 410 | 1/4" M | 800 mm | 1/2" M | stainless steel |
| 203 600 412 | 1/4" M | 1000 mm | 1/2" M | stainless steel |

| R+M Nr. |
|---------|
| |
| |

Symbols ☺ outlet ☹ inlet ☹ length ISO insulation M material D nozzle