

CARWASH COMFORT - the new hose wonder in self-service washing bays



Female thread (DKR)

Female thread (DKR)

Female thread (DKOL)

Female thread (DKOL)

Male thread (AGR)

R+M Nr.	↔	length
463 052 703 5		3.5 m
463 052 703 7		3.7 m
463 052 704		4.0 m
463 052 704 2		4.2 m
463 052 704 5		4.5 m
463 052 704 7		4.7 m
463 052 705		5.0 m
463 052 705 5		5.5 m
463 052 706		6.0 m

R+M Nr.	↔	length
463 054 703 5		3.5 m
463 054 703 7		3.7 m
463 054 704		4.0 m
463 054 704 2		4.2 m
463 054 704 5		4.5 m
463 054 704 7		4.7 m
463 054 705		5.0 m
463 054 705 5		5.5 m
463 054 706		6.0 m

R+M Nr.	↔	length
463 072 703 5		3.5 m
463 072 703 7		3.7 m
463 072 704		4.0 m
463 072 704 2		4.2 m
463 072 704 5		4.5 m
463 072 704 7		4.7 m
463 072 705		5.0 m
463 072 705 5		5.5 m
463 072 706		6.0 m

R+M Nr.	↔	length
463 076 703 5		3.5 m
463 076 703 7		3.7 m
463 076 704		4.0 m
463 076 704 2		4.2 m
463 076 704 5		4.5 m
463 076 704 7		4.7 m
463 076 705		5.0 m
463 076 705 5		5.5 m
463 076 706		6.0 m

R+M Nr.	↔	length
463 044 703 5		3.5 m
463 044 703 7		3.7 m
463 044 704		4.0 m
463 044 704 2		4.2 m
463 044 704 5		4.5 m
463 044 704 7		4.7 m
463 044 705		5.0 m
463 044 705 5		5.5 m
463 044 706		6.0 m



Female thread (DKR)

Female thread (DKR)

Female thread (DKOL)

Female thread (DKOL)

Male thread (AGR)

R+M Nr.	↔	length
464 052 303 5		3.5 m
464 052 303 7		3.7 m
464 052 304		4.0 m
464 052 304 2		4.2 m
464 052 304 5		4.5 m
464 052 304 7		4.7 m
464 052 305		5.0 m
464 052 305 5		5.5 m
464 052 306		6.0 m

R+M Nr.	↔	length
464 054 303 5		3.5 m
464 054 303 7		3.7 m
464 054 304		4.0 m
464 054 304 2		4.2 m
464 054 304 5		4.5 m
464 054 304 7		4.7 m
464 054 305		5.0 m
464 054 305 5		5.5 m
464 054 306		6.0 m

R+M Nr.	↔	length
464 072 303 5		3.5 m
464 072 303 7		3.7 m
464 072 304		4.0 m
464 072 304 2		4.2 m
464 072 304 5		4.5 m
464 072 304 7		4.7 m
464 072 305		5.0 m
464 072 305 5		5.5 m
464 072 306		6.0 m

R+M Nr.	↔	length
464 076 303 5		3.5 m
464 076 303 7		3.7 m
464 076 304		4.0 m
464 076 304 2		4.2 m
464 076 304 5		4.5 m
464 076 304 7		4.7 m
464 076 305		5.0 m
464 076 305 5		5.5 m
464 076 306		6.0 m

R+M Nr.	↔	length
464 044 303 5		3.5 m
464 044 303 7		3.7 m
464 044 304		4.0 m
464 044 304 2		4.2 m
464 044 304 5		4.5 m
464 044 304 7		4.7 m
464 044 305		5.0 m
464 044 305 5		5.5 m
464 044 306		6.0 m



Female thread (DKR)

Female thread (DKR)

Female thread (DKOL)

Female thread (DKOL)

Male thread (AGR)

R+M Nr.	↔	length
465 052 303 5		3.5 m
465 052 303 7		3.7 m
465 052 304		4.0 m
465 052 304 2		4.2 m
465 052 304 5		4.5 m
465 052 304 7		4.7 m
465 052 305		5.0 m
465 052 305 5		5.5 m
465 052 306		6.0 m

R+M Nr.	↔	length
465 054 303 5		3.5 m
465 054 303 7		3.7 m
465 054 304		4.0 m
465 054 304 2		4.2 m
465 054 304 5		4.5 m
465 054 304 7		4.7 m
465 054 305		5.0 m
465 054 305 5		5.5 m
465 054 306		6.0 m

R+M Nr.	↔	length
465 072 303 5		3.5 m
465 072 303 7		3.7 m
465 072 304		4.0 m
465 072 304 2		4.2 m
465 072 304 5		4.5 m
465 072 304 7		4.7 m
465 072 305		5.0 m
465 072 305 5		5.5 m
465 072 306		6.0 m

R+M Nr.	↔	length
465 076 303 5		3.5 m
465 076 303 7		3.7 m
465 076 304		4.0 m
465 076 304 2		4.2 m
465 076 304 5		4.5 m
465 076 304 7		4.7 m
465 076 305		5.0 m
465 076 305 5		5.5 m
465 076 306		6.0 m

R+M Nr.	↔	length
465 044 303 5		3.5 m
465 044 303 7		3.7 m
465 044 304		4.0 m
465 044 304 2		4.2 m
465 044 304 5		4.5 m
465 044 304 7		4.7 m
465 044 305		5.0 m
465 044 305 5		5.5 m
465 044 306		6.0 m

Symbols ↔ length