

Suttner tank cleaner

ST-82 h16/40 self rotating tank cleaner



- » Inlet: 1/2" F
- » Pressure: 40 - 160 bar
- » Flow: 20 - 30 l / min
- » Temperature: 0 - 90 °C
- » Turns: 29 - 36 r.p.m
- » Beam coverage 244°
- » Weight: 3,6 kg
- » 3 nozzles needed 1/8" M NPT
- » Other versions on request 20-50 l/min

R+M Nr.	D	←	P
200 082 600	basic version without nozzle		
200 082 601	3 x 060	40 l/min	100 bar
200 082 602	3 x 030	21 l/min	110 bar
200 082 603	3 x 040	30 l/min	140 bar

ST-82 h16/120 self rotating tank cleaner



- » Inlet: 3/4" F
- » Pressure: 30 - 160 bar
- » Flow: 20 - 120 l/min
- » Temperature: 0 - 90 °C
- » Turns: 10 - 16 r.p.m
- » Beam coverage 360°
- » Weight: 5,9 kg
- » 2 nozzles and 2 caps needed, max. 4 nozzles 1/4 " M NPT

R+M Nr.	D	←	P
200 082 700	basic version without nozzle		
200 082 717	2 x 110	42 l/min	70 bar
200 082 713	2 x 120	50 l/min	80 bar
200 082 701	2 x 075	34 l/min	100 bar
200 082 709	4 x 050	45 l/min	100 bar
200 082 708	2 x 110 *	48 l/min	100 bar
200 082 705	4 x 055 *	50 l/min	100 bar
200 082 702	2 x 060	27 l/min	100 bar
200 082 710	4 x 045	42 l/min	120 bar
200 082 716	4 x 070	67 l/min	120 bar
200 082 712	2 x 050	25 l/min	130 bar
200 082 704	2 x 040	21 l/min	140 bar
200 082 703	2 x 045	22 l/min	140 bar
200 082 706	2 x 060	32 l/min	140 bar
200 082 711	4 x 040 *	40 l/min	140 bar
200 082 714	-	50-60 l/min	140 bar
200 082 715	2 x 055	28 l/min	140 bar
200 082 718	2 x 065*	35 l/min	140 bar
200 082 707	4 x 040	45 l/min	160 bar

* with protection cage

Please specify pressure & flow rate with your order.
The tank cleaner are individually assembled to your needs.