

easyfarm365+



LTF

Professional gun with coupling KW.
Max. 250 bar / 60 l/min / 150 °C

R+M Nr.			
202 620 655	coupling KW	1/2" F swivel	



LTF

Professional gun with coupling ST-3100.
Max. 250 bar / 60 l/min / 150 °C

R+M Nr.			
202 620 650	coupling ST-3100	1/2" F swivel	

ST-340 swivels



1/4" F : 1/2" F



Repair kit ST-340

R+M Nr.
200 340 520

R+M Nr.
200 340 150

LTF - Low Trigger Force 90 % reduced holding force and 40 % reduced trigger force against usual market guns.

Grips



Grip for lances with
moulded handle

R+M Nr.
200 009 700



Grip for ST-85
Push & Pull lances

R+M Nr.
200 009 680

Protector ST-10



1/4" F. Plastic. Stainless
steel

R+M Nr.
200 010 760

Suitable high pressure hoses are
on page 148 and 155.

ST-85 Push & Pull lances



Plug KW. Lance stainless steel, vented handle ST-9 380 mm and nozzle protector ST-10 without nozzle. Variable adjustment of spraying angle from 20 to 140°. Especially designed for cleaning of places which are difficult to access. Max. 210 bar / 150 °C

R+M Nr.			
200 085 253	1/4" F NPT	600 mm	plug KW
200 085 613	1/4" F NPT	850 mm	plug KW
200 085 603	1/4" F NPT	1,000 mm	plug KW
200 085 653	1/4" F NPT	1,500 mm	plug KW